

More Math Into L^AT_EX

4th Edition

George Grätzer

More Math Into L^AT_EX

4th Edition

Foreword by
Rainer Schöpf
L^AT_EX3 team

 Springer

George Grätzer
Department of Mathematics
University of Manitoba
Winnipeg, MB R3T 2N2
Canada
gratzer@ms.umanitoba.ca

Cover design by Mary Burgess.
Typeset by the author in L^AT_EX.

Library of Congress Control Number: 2007923503

ISBN-13: 978-387-32289-6 e-ISBN-13: 978-0-387-68852-7

Printed on acid-free paper.

©2007 Springer Science+Business Media, LLC

All rights reserved. This work may not be translated or copied in whole or in part without the written permission of the publisher (Springer Science+Business Media LLC, 233 Spring Street, New York, NY 10013, USA) and the author, except for brief excerpts in connection with reviews or scholarly analysis. Use in connection with any form of information storage and retrieval, electronic adaptation, computer software, or by similar or dissimilar methodology now known or hereafter developed is forbidden.

The use in this publication of trade names, trademarks, service marks and similar terms, even if they are not identified as such, is not to be taken as an expression of opinion as to whether or not they are subject to proprietary rights.

9 8 7 6 5 4 3 2 1

springer.com

(HP)

To the **Volunteers**
without whose dedication over 15 years,
this book could not have been done

and to my four grandchildren
Danny (11),
Anna (8),
Emma (2),
and **Kate** (0)

Short Contents

Foreword	xxi
Preface to the Fourth Edition	xxv
Introduction	xxix
I Short Course	1
1 Your L ^A T _E X	3
2 Typing text	7
3 Typing math	17
4 Your first article and presentation	35
II Text and Math	59
5 Typing text	61
6 Text environments	117
7 Typing math	151
8 More math	187
9 Multiline math displays	207

III Document Structure	245
10 L ^A T _E X documents	247
11 The AMS article document class	271
12 Legacy document classes	303
IV Presentations and PDF Documents	315
13 PDF documents	317
14 Presentations	325
V Customization	361
15 Customizing L ^A T _E X	363
VI Long Documents	419
16 B _I B _T E _X	421
17 <i>MakeIndex</i>	449
18 Books in L ^A T _E X	465
A Installation	489
B Math symbol tables	501
C Text symbol tables	515
D Some background	521
E L^AT_EX and the Internet	537
F PostScript fonts	543
G L^AT_EX localized	547
H Final thoughts	551
Bibliography	557
Index	561

Contents

Foreword	xxi
Preface to the Fourth Edition	xxv
Acknowledgments	xxvii
Introduction	xxix
Is this book for you?	xxix
I Short Course	1
1 Your L^AT_EX	3
1.1 Your computer	3
1.2 Sample files	4
1.3 Editing cycle	4
1.4 Three productivity tools	5
2 Typing text	7
2.1 The keyboard	8
2.2 Your first note	9
2.3 Lines too wide	12
2.4 More text features	13
3 Typing math	17
3.1 A note with math	17
3.2 Errors in math	19
3.3 Building blocks of a formula	22
3.4 Displayed formulas	27
3.4.1 Equations	27

3.4.2	Aligned formulas	30
3.4.3	Cases	33
4	Your first article and presentation	35
4.1	The anatomy of an article	35
4.1.1	The typeset sample article	41
4.2	An article template	44
4.2.1	Editing the top matter	44
4.2.2	Sectioning	46
4.2.3	Invoking proclamations	46
4.2.4	Inserting references	47
4.3	On using \LaTeX	48
4.3.1	\LaTeX error messages	48
4.3.2	Logical and visual design	52
4.4	Converting an article to a presentation	53
4.4.1	Preliminary changes	53
4.4.2	Making the pages	55
4.4.3	Fine tuning	55
II	Text and Math	59
5	Typing text	61
5.1	The keyboard	62
5.1.1	Basic keys	62
5.1.2	Special keys	63
5.1.3	Prohibited keys	63
5.2	Words, sentences, and paragraphs	64
5.2.1	Spacing rules	64
5.2.2	Periods	66
5.3	Commanding \LaTeX	67
5.3.1	Commands and environments	68
5.3.2	Scope	71
5.3.3	Types of commands	73
5.4	Symbols not on the keyboard	74
5.4.1	Quotation marks	75
5.4.2	Dashes	75
5.4.3	Ties or nonbreakable spaces	76
5.4.4	Special characters	76
5.4.5	Ellipses	78
5.4.6	Ligatures	79
5.4.7	Accents and symbols in text	79
5.4.8	Logos and dates	80

5.4.9	Hyphenation	82
5.5	Comments and footnotes	85
5.5.1	Comments	85
5.5.2	Footnotes	87
5.6	Changing font characteristics	88
5.6.1	Basic font characteristics	88
5.6.2	Document font families	89
5.6.3	Shape commands	90
5.6.4	Italic corrections	91
5.6.5	Series	93
5.6.6	Size changes	93
5.6.7	Orthogonality	94
5.6.8	Obsolete two-letter commands	94
5.6.9	Low-level commands	95
5.7	Lines, paragraphs, and pages	95
5.7.1	Lines	96
5.7.2	Paragraphs	99
5.7.3	Pages	100
5.7.4	Multicolumn printing	101
5.8	Spaces	102
5.8.1	Horizontal spaces	102
5.8.2	Vertical spaces	104
5.8.3	Relative spaces	105
5.8.4	Expanding spaces	106
5.9	Boxes	107
5.9.1	Line boxes	107
5.9.2	Frame boxes	109
5.9.3	Paragraph boxes	110
5.9.4	Marginal comments	112
5.9.5	Solid boxes	113
5.9.6	Fine tuning boxes	115
6	Text environments	117
6.1	Some general rules for displayed text environments	118
6.2	List environments	118
6.2.1	Numbered lists	119
6.2.2	Bulleted lists	119
6.2.3	Captioned lists	120
6.2.4	A rule and combinations	120
6.3	Style and size environments	123
6.4	Proclamations (theorem-like structures)	124
6.4.1	The full syntax	128

6.4.2	Proclamations with style	129
6.5	Proof environments	131
6.6	Tabular environments	133
6.6.1	Table styles	140
6.7	Tabbing environments	141
6.8	Miscellaneous displayed text environments	143
7	Typing math	151
7.1	Math environments	152
7.2	Spacing rules	154
7.3	Equations	156
7.4	Basic constructs	157
7.4.1	Arithmetic operations	157
7.4.2	Binomial coefficients	159
7.4.3	Ellipses	160
7.4.4	Integrals	161
7.4.5	Roots	161
7.4.6	Text in math	162
7.4.7	Building a formula step-by-step	164
7.5	Delimiters	166
7.5.1	Stretching delimiters	167
7.5.2	Delimiters that do not stretch	168
7.5.3	Limitations of stretching	169
7.5.4	Delimiters as binary relations	170
7.6	Operators	170
7.6.1	Operator tables	171
7.6.2	Defining operators	173
7.6.3	Congruences	173
7.6.4	Large operators	174
7.6.5	Multiline subscripts and superscripts	176
7.7	Math accents	176
7.8	Stretchable horizontal lines	178
7.8.1	Horizontal braces	178
7.8.2	Overlines and underlines	179
7.8.3	Stretchable arrow math symbols	179
7.9	Formula Gallery	180
8	More math	187
8.1	Spacing of symbols	187
8.1.1	Classification	188
8.1.2	Three exceptions	188
8.1.3	Spacing commands	190
8.1.4	Examples	190

8.1.5	The phantom command	191
8.2	Building new symbols	192
8.2.1	Stacking symbols	192
8.2.2	Negating and side-setting symbols	194
8.2.3	Changing the type of a symbol	195
8.3	Math alphabets and symbols	195
8.3.1	Math alphabets	196
8.3.2	Math symbol alphabets	197
8.3.3	Bold math symbols	197
8.3.4	Size changes	199
8.3.5	Continued fractions	200
8.4	Vertical spacing	200
8.5	Tagging and grouping	201
8.6	Miscellaneous	204
8.6.1	Generalized fractions	204
8.6.2	Boxed formulas	205
9	Multiline math displays	207
9.1	Visual Guide	207
9.1.1	Columns	209
9.1.2	Subsidiary math environments	209
9.1.3	Adjusted columns	210
9.1.4	Aligned columns	210
9.1.5	Touring the Visual Guide	210
9.2	Gathering formulas	211
9.3	Splitting long formulas	212
9.4	Some general rules	215
9.4.1	General rules	215
9.4.2	Subformula rules	215
9.4.3	Breaking and aligning formulas	217
9.4.4	Numbering groups of formulas	218
9.5	Aligned columns	219
9.5.1	An align variant	221
9.5.2	eqnarray, the ancestor of align	222
9.5.3	The subformula rule revisited	223
9.5.4	The alignat environment	224
9.5.5	Inserting text	226
9.6	Aligned subsidiary math environments	227
9.6.1	Subsidiary variants	227
9.6.2	Split	230
9.7	Adjusted columns	231
9.7.1	Matrices	232

9.7.2	Arrays	236
9.7.3	Cases	239
9.8	Commutative diagrams	240
9.9	Adjusting the display	242

III Document Structure 245

10 L^AT_EX documents 247

10.1	The structure of a document	248
10.2	The preamble	249
10.3	Top matter	251
10.3.1	Abstract	251
10.4	Main matter	251
10.4.1	Sectioning	252
10.4.2	Cross-referencing	255
10.4.3	Floating tables and illustrations	258
10.5	Back matter	261
10.5.1	Bibliographies in articles	261
10.5.2	Simple indexes	267
10.6	Visual design	268

11 The AMS article document class 271

11.1	Why <code>amsart</code> ?	271
11.1.1	Submitting an article to the AMS	271
11.1.2	Submitting an article to Algebra Universalis	272
11.1.3	Submitting to other journals	272
11.1.4	Submitting to conference proceedings	273
11.2	The top matter	273
11.2.1	Article information	273
11.2.2	Author information	275
11.2.3	AMS information	279
11.2.4	Multiple authors	281
11.2.5	Examples	282
11.2.6	Abstract	285
11.3	The sample article	285
11.4	Article templates	294
11.5	Options	297
11.6	The AMS packages	300

12 Legacy document classes	303
12.1 Articles and reports	303
12.1.1 Top matter	304
12.1.2 Options	306
12.2 Letters	308
12.3 The L ^A T _E X distribution	310
12.3.1 Tools	312
IV Presentations and PDF Documents	315
13 PDF documents	317
13.1 PostScript and PDF	317
13.1.1 PostScript	317
13.1.2 PDF	318
13.1.3 Hyperlinks	319
13.2 Hyperlinks for L ^A T _E X	319
13.2.1 Using hyperref	320
13.2.2 backref and colorlinks	320
13.2.3 Bookmarks	321
13.2.4 Additional commands	322
14 Presentations	325
14.1 Quick and dirty beamer	326
14.1.1 First changes	326
14.1.2 Changes in the body	327
14.1.3 Making things prettier	328
14.1.4 Adjusting the navigation	328
14.2 Baby beamers	333
14.2.1 Overlays	333
14.2.2 Understanding overlays	335
14.2.3 More on the \only and \onslide commands	337
14.2.4 Lists as overlays	339
14.2.5 Out of sequence overlays	341
14.2.6 Blocks and overlays	343
14.2.7 Links	343
14.2.8 Columns	347
14.2.9 Coloring	348
14.3 The structure of a presentation	350
14.3.1 Longer presentations	354
14.3.2 Navigation symbols	354
14.4 Notes	355
14.5 Themes	356

14.6	Planning your presentation	358
14.7	What did I leave out?	358

V Customization 361

15 Customizing L^AT_EX 363

15.1	User-defined commands	364
15.1.1	Examples and rules	364
15.1.2	Arguments	370
15.1.3	Short arguments	373
15.1.4	Optional arguments	374
15.1.5	Redefining commands	374
15.1.6	Redefining names	375
15.1.7	Showing the definitions of commands	376
15.1.8	Delimited commands	378
15.2	User-defined environments	380
15.2.1	Modifying existing environments	380
15.2.2	Arguments	383
15.2.3	Optional arguments with default values	384
15.2.4	Short contents	385
15.2.5	Brand-new environments	385
15.3	A custom command file	386
15.4	The sample article with user-defined commands	392
15.5	Numbering and measuring	398
15.5.1	Counters	399
15.5.2	Length commands	403
15.6	Custom lists	406
15.6.1	Length commands for the list environment	407
15.6.2	The list environment	409
15.6.3	Two complete examples	411
15.6.4	The trivlist environment	414
15.7	The dangers of customization	415

VI Long Documents 419

16 B^IB_TE_X 421

16.1	The database	423
16.1.1	Entry types	423
16.1.2	Typing fields	426
16.1.3	Articles	428
16.1.4	Books	429

16.1.5	Conference proceedings and collections	430
16.1.6	Theses	433
16.1.7	Technical reports	434
16.1.8	Manuscripts and other entry types	435
16.1.9	Abbreviations	436
16.2	Using <code>BIBTEX</code>	437
16.2.1	Sample files	437
16.2.2	Setup	439
16.2.3	Four steps of <code>BIBTEXing</code>	440
16.2.4	<code>BIBTEX</code> rules and messages	443
16.2.5	Submitting an article	446
16.3	Concluding comments	446
17	<i>MakeIndex</i>	449
17.1	Preparing the document	449
17.2	Index commands	453
17.3	Processing the index entries	459
17.4	Rules	462
17.5	Multiple indexes	463
17.6	Glossary	464
17.7	Concluding comments	464
18	Books in <code>L^AT_EX</code>	465
18.1	Book document classes	466
18.1.1	Sectioning	466
18.1.2	Division of the body	467
18.1.3	Document class options	468
18.1.4	Title pages	469
18.1.5	Springer's document class for monographs	469
18.2	Tables of contents, lists of tables and figures	473
18.2.1	Tables of contents	473
18.2.2	Lists of tables and figures	475
18.2.3	Exercises	476
18.3	Organizing the files for a book	476
18.3.1	The folders and the master document	477
18.3.2	Inclusion and selective inclusion	478
18.3.3	Organizing your files	479
18.4	Logical design	479
18.5	Final preparations for the publisher	482
18.6	If you create the PDF file for your book	484

A	Installation	489
A.1	\LaTeX on a PC	490
A.1.1	Installing MiKTeX	490
A.1.2	Installing WinEdt	490
A.1.3	The editing cycle	491
A.1.4	Making a mistake	491
A.1.5	Three productivity tools	494
A.1.6	An important folder	494
A.2	\LaTeX on a Mac	495
A.2.1	Installations	495
A.2.2	Working with TeXShop	496
A.2.3	The editing cycle	498
A.2.4	Making a mistake	498
A.2.5	Three productivity tools	498
A.2.6	An important folder	499
B	Math symbol tables	501
B.1	Hebrew and Greek letters	501
B.2	Binary relations	503
B.3	Binary operations	506
B.4	Arrows	507
B.5	Miscellaneous symbols	508
B.6	Delimiters	509
B.7	Operators	510
B.7.1	Large operators	511
B.8	Math accents and fonts	512
B.9	Math spacing commands	513
C	Text symbol tables	515
C.1	Some European characters	515
C.2	Text accents	516
C.3	Text font commands	516
C.3.1	Text font family commands	516
C.3.2	Text font size changes	517
C.4	Additional text symbols	518
C.5	Additional text symbols with T1 encoding	519
C.6	Text spacing commands	520
D	Some background	521
D.1	A short history	521
D.1.1	\TeX	521
D.1.2	\LaTeX 2.09 and $\mathcal{A}\mathcal{M}\mathcal{S}\text{-}\TeX$	522
D.1.3	\LaTeX 3	523

D.1.4	More recent developments	524
D.2	Structure	525
D.2.1	Using L ^A T _E X	525
D.2.2	AMS packages revisited	528
D.3	How L ^A T _E X works	528
D.3.1	The layers	528
D.3.2	Typesetting	529
D.3.3	Viewing and printing	530
D.3.4	L ^A T _E X's files	531
D.4	Interactive L ^A T _E X	534
D.5	Separating form and content	535
E	L^AT_EX and the Internet	537
E.1	Obtaining files from the Internet	537
E.2	The T _E X Users Group	541
E.3	Some useful sources of L ^A T _E X information	542
F	PostScript fonts	543
F.1	The Times font and MathTime	544
F.2	Lucida Bright fonts	546
F.3	More PostScript fonts	546
G	L^AT_EX localized	547
H	Final thoughts	551
H.1	What was left out?	551
H.1.1	L ^A T _E X omissions	551
H.1.2	T _E X omissions	552
H.2	Further reading	553
H.3	What's coming	554
	Bibliography	557
	Index	561

Foreword

It was the autumn of 1989—a few weeks before the Berlin wall came down, President George H. W. Bush was president, and the American Mathematical Society decided to outsource T_EX programming to Frank Mittelbach and me.

Why did the AMS outsource T_EX programming to us? This was, after all, a decade before the words “outsourcing” and “off-shore” entered the lexicon. There were many American T_EX experts. Why turn elsewhere?

For a number of years, the AMS tried to port the mathematical typesetting features of $\mathcal{A}\mathcal{M}\mathcal{S}$ -T_EX to L_AT_EX, but they made little progress with the AMSFonts. Frank and I had just published the New Font Selection Scheme for L_AT_EX, which went a long way to satisfy what they wanted to accomplish. So it was logical that the AMS turned to us to add AMSFonts to L_AT_EX. Being young and enthusiastic, we convinced the AMS that the $\mathcal{A}\mathcal{M}\mathcal{S}$ -T_EX commands should be changed to conform to the L_AT_EX standards. Michael Downes was assigned as our AMS contact; his insight was a tremendous help.

We already had L_AT_EX-NFSS, which could be run in two modes: compatible with the old L_AT_EX or enabled with the new font features. We added the reworked $\mathcal{A}\mathcal{M}\mathcal{S}$ -T_EX code to L_AT_EX-NFSS, thus giving birth to $\mathcal{A}\mathcal{M}\mathcal{S}$ -L_AT_EX, released by the AMS at the August 1990 meeting of the International Mathematical Union in Kyoto.

$\mathcal{A}\mathcal{M}\mathcal{S}$ -L_AT_EX was another variant of L_AT_EX. Many installations had several L_AT_EX variants to satisfy the needs of their users: with old and new font changing commands, with and without $\mathcal{A}\mathcal{M}\mathcal{S}$ -L_AT_EX, a single and a multi-language version. We decided to develop a Standard L_AT_EX that would reconcile all the variants. Out of a group of interested people grew what was later called the *L_AT_EX3 team*—and the L_AT_EX3 project got underway. The team’s first major accomplishment was the release of L_AT_EX 2_ε in June 1994. This standard L_AT_EX incorporates all the improvements we wanted back in 1989. It is now very stable and it is uniformly used.

Under the direction of Michael Downes, our $\mathcal{A}\mathcal{M}\mathcal{S}$ -L_AT_EX code was turned into AMS packages that run under L_AT_EX just like other packages. Of course, the L_AT_EX3

team recognizes that these are special; we call them “required packages” because they are part and parcel of a mathematician’s standard toolbox.

Since then a lot has been achieved to make an author’s task easier. A tremendous number of additional packages are available today. The *L^AT_EX Companion*, 2nd edition, describes many of my favorite packages.

George Grätzer got involved with these developments in 1990, when he got his copy of $\mathcal{A}\mathcal{M}\mathcal{S}$ -L^AT_EX in Kyoto. The documentation he received explained that $\mathcal{A}\mathcal{M}\mathcal{S}$ -L^AT_EX is a L^AT_EX variant—read Lamport’s L^AT_EX book to get the proper background. $\mathcal{A}\mathcal{M}\mathcal{S}$ -L^AT_EX is not $\mathcal{A}\mathcal{M}\mathcal{S}$ -T_EX either—read Spivak’s $\mathcal{A}\mathcal{M}\mathcal{S}$ -T_EX book to get the proper background. The rest of the document explained in what way $\mathcal{A}\mathcal{M}\mathcal{S}$ -L^AT_EX differs from L^AT_EX and $\mathcal{A}\mathcal{M}\mathcal{S}$ -T_EX. Talk about a steep learning curve . . .

Luckily, George’s frustration working through this nightmare was eased by a lengthy e-mail correspondence with Frank and lots of telephone calls to Michael. Three years of labor turned into his first book on L^AT_EX, providing a “simple introduction to $\mathcal{A}\mathcal{M}\mathcal{S}$ -L^AT_EX”.

This fourth edition is more mature, but preserves what made his first book such a success. Just as in the first book, Part I is a short introduction for the beginner, dramatically reducing the steep learning curve of a few weeks to a few hours. The rest of the book is a detailed presentation of what you may need to know. George “teaches by example”. You find in this book many illustrations of even the simplest concepts. For articles, he presents the L^AT_EX source file and the typeset result side-by-side. For formulas, he discusses the building blocks with examples, presents a *Formula Gallery*, and a *Visual Guide* to multiline formulas.

Going forth and creating “masterpieces of the typesetting art”—as Donald Knuth put it at the end of the *T_EXbook*—requires a fair bit of initiation. This is the book for the L^AT_EX beginner as well as for the advanced user. You just start at a different point.

The topics covered include everything you need for mathematical publishing.

- Starting from scratch, by installing and running L^AT_EX on your own computer
- Instructions on creating articles, from the simple to the complex
- Converting an article to a presentation
- Customize L^AT_EX to your own needs
- The secrets of writing a book
- Where to turn to get more information or to download updates

The many examples are complemented by a number of easily recognizable features:

Rules which you must follow

Tips on how to achieve some specific results

Experiments to show what happens when you make mistakes—sometimes, it can be difficult to understand what went wrong when all you see is an obscure L^AT_EX error message

This book teaches you how to convert your mathematical masterpieces into typographical ones, giving you a lot of useful advice on the way. How to avoid the traps for the unwary and how to make your editor happy. And hopefully, you'll experience the fascination of doing it right. Using good typography to better express your ideas.

If you want to learn \LaTeX , buy this book and start with the *Short Course*. If you can have only one book on \LaTeX next to your computer, this is the one to have. And if you want to learn about the world of \LaTeX packages, also buy a second book, the *\LaTeX Companion*, 2nd edition.

A handwritten signature in black ink that reads "Rainer Schöpf". The script is cursive and elegant, with the first letters of "Rainer" and "Schöpf" being capitalized and prominent.

Rainer Schöpf
 \LaTeX 3 team

Preface to the Fourth Edition

This is my fourth full-sized book on \LaTeX .

The first book, *Math into $T_{\text{E}}X$: A Simple Introduction to $\mathcal{A}\mathcal{M}\mathcal{S}$ - \LaTeX* [19], written in 1991 and 1992, introduced the brand new $\mathcal{A}\mathcal{M}\mathcal{S}$ - \LaTeX , a \LaTeX variant not compatible with the \LaTeX of the time, \LaTeX 2.09. It brought together the features of \LaTeX and the math typesetting abilities of $\mathcal{A}\mathcal{M}\mathcal{S}$ - $T_{\text{E}}X$, the AMS typesetting language.

The second book, *Math into \LaTeX : An Introduction to \LaTeX and $\mathcal{A}\mathcal{M}\mathcal{S}$ - \LaTeX* [27], written in 1995, describes the new \LaTeX introduced by the \LaTeX 3 team and the AMS typesetting features implemented as extensions of \LaTeX , called packages.

The third book, *Math into \LaTeX* , 3rd edition [30], published in 2000, reports on the same system. By 2000, both the “new” \LaTeX and the AMS packages were quite mature. The feverish debugging of the new \LaTeX every six months bore fruit. \LaTeX became very stable. It has changed little since 2000. Version 2.0 of the AMS packages was released and it also became very stable. The third book reports on a rock solid typesetting system.

What also changed between 1995 and 2000 is the widespread use of the Internet. Several chapters of the third book deal with the impact of the Internet on mathematical publications.

Now, seven years later, we can still report that \LaTeX —no longer new—and the AMS packages have changed very little. However, the impact of the Internet became even more important. Computers also changed. They are now much more powerful. When I started typesetting math with \LaTeX , it took two and a half minutes to typeset a page. This book takes 1.8 seconds to typeset on my computer, a Mac desktop from 2006. As a result, we do not have to be very selective in what we load into memory; we can load everything we may possibly need.

Circumincission

So this is the first big change compared to the previous books. In this book, we roll \TeX , \LaTeX , and the AMS packages into one, and we call it simply \LaTeX . This results in a great simplification in the exposition and makes the learning curve a little less steep.

I am sure with some advanced users this will prove to be a controversial decision. They want to know where a command is defined. For the beginner and the non-expert user this does not make any difference. What matters is that the command they need be available when they need it.

From the beginner's point of view, this approach is very beneficial. Take as an example the `\text` command. In all three of my books, we first introduce the \LaTeX command `\mbox` for typing text in math formulas. After half a page of discussion comes the sentence: "It is better to enter text in formulas with the `\text` command provided by the `amsmath` package." Then another half page discusses the command `\text`. In this book, we ignore `\mbox` and go right-away to `\text`. You do not have to do anything to access the command, the `amsmath` package is always loaded for you.

And what to do if you want to find out where a command is defined. Now for both the PC and the Mac, you can easily search for contents of files. Do you want to know where a command is defined? Search for it and it is easy to find the file in which it is introduced.

Presentations

The second big change is the widespread acceptance of the Adobe PDF format. As a result, the majority of the lectures today at math meetings are given as *presentations*, PDF files projected to screens using computers. Blackboards and whiteboards have largely disappeared and computer projections are overtaking projectors. So this book takes up presentations as a major topic, introducing it in Part I and discussing it in detail in Chapter 14.

Installations

In the third book, I report a recurring question that comes up from my readers again and again:

Can you help me get started from scratch, covering everything from installing a working \LaTeX system to the rudiments of text editing?

And here is the third big change that has happened in the last few years. While earlier there were dozens of different \LaTeX implementations and hundreds of text editors, today most PC users use MiKTeX with the text editor/front end `WinEdt` and most Mac users use \TeX Live with the text editor/front end `TeXShop`. So if you want help to

install L^AT_EX, it is easy for me to help you. Appendix A provides instructions on how to install these systems.

Acknowledgments

This book is based, of course, on the three previous books. I would like to thank the many people who read and reread those earlier manuscripts.

The editors Richard Ribstein, Thomas R. Scavo, Claire M. Connelly.

The professionals Michael Downes (the project leader for the AMS), Frank Mittelbach and David Carlisle (of the L^AT_EX3 team) read and criticized some or all of the three books.

Oren Patashnik (the author of B^IB_TE_X) carefully corrected the B^IB_TE_X chapter for two editions.

Sebastian Rahtz (the author of the `hyperref` package and coauthor of *The L^AT_EX Web Companion* [18]) read the chapter on the Web in the third book.

Last but not least, Barbara Beeton of the AMS read all three books with incredible insight.

The volunteers for the second book alone, there were 29—listed there. The volunteer readers made tremendous contributions and offered hundreds of pages of corrections. No expert can substitute for the diverse points of view I got from them.

My colleagues especially Michael Doob, Harry Lakser, and Craig Platt, who have been very generous with their time.

The publishers Edwin Beschler, who believed in the project from the very beginning and guided it through a decade and Ann Kostant who continued Edwin's work.

For this book, I have had the most talented and thorough group of readers ever: Andrew Adler of the University of British Columbia, Canada, Joseph Maria Font of the University of Barcelona, Spain, and Alan Litchfield, of the Auckland University of Technology, New Zealand. Chapter 14 was read by David Derbes, Adam Goldstein, Mark Eli Kalderon, Michael Kubovy, Matthieu Masquelet, and Charilaos Skiadas—and Chapter 15 by Ross Moore. Interestingly, only half of them are mathematicians, the rest are philosophers, linguists, and so on. Appendix A.1 was read by Brian Davey and Appendix A.2 by Richard Koch (the author of `TeXShop`).

The fourth edition was edited by Barbara Beeton, Edwin Beschler, and Clay Martin with Ann Kostant as the Springer editor. The roles of Edwin and Ann have changed, but not the importance of their contributions. The index was compiled with painstaking precision by Laura Kirkland. Barbara Beeton also provided a number of intriguing illustrations of quaint commands. My indebtedness to her cannot be overstated.

George Grätzer

Introduction

Is this book for you?

This book is for the mathematician, physicist, engineer, scientist, linguist, or technical typist who has to learn how to typeset articles containing mathematical formulas or diacritical marks. It teaches you how to use \LaTeX , a typesetting markup language based on Donald E. Knuth's typesetting language \TeX , designed and implemented by Leslie Lamport, and greatly improved by the AMS.

Part I provides a quick introduction to \LaTeX , from typing examples of text and math to typing your first article (such as the sample article on pages 42–43) and creating your first presentation (such as the sample presentation on pages 57–58) in a very short time. The rest of the book provides a detailed exposition of \LaTeX .

\LaTeX has a huge collection of rules and commands. While the basics in Part I should serve you well in all your writings, most articles and presentations also require you to look up special topics. Learn Part I well and become passingly familiar enough with the rest of the book, so when the need arises you know where to turn with your problems.

You can find specific topics in one or more of the following sources: the Short Contents, the detailed Contents, and the Index.

What is document markup?

When you work with a word processor, you see your document on the computer monitor more or less as it looks when printed, with its various fonts, font sizes, font shapes (e.g., roman, italic) and weights (e.g., normal, boldface), interline spacing, indentation, and so on.

Working with a *markup language* is different. You type the *source file* of your article in a *text editor*, in which all characters appear in the same font. To indicate changes in the typeset text, you must add *text markup commands* to the source file.

For instance, to emphasize the phrase `detailed description` in a \LaTeX source file, type

```
\emph{detailed description}
```

The `\emph` command is a markup command. The marked-up text yields the typeset output

```
┌
  detailed description
└
```

In order to typeset math, you need *math markup commands*. As a simple example, you may need the formula $\int \sqrt{\alpha^2 + x^2} dx$ in an article you are writing. To mark up this formula in \LaTeX , type

```
$\int \sqrt{\alpha^2 + x^2} \, dx$
```

You do not have to worry about determining the size of the integral symbol or how to construct the square root symbol that covers $\alpha^2 + x^2$. \LaTeX does it all for you.

On pages 290–293, I juxtapose the source file for a sample article with the typeset version. The markup in the source file may appear somewhat challenging at first, but I think you agree that the typeset article is a pleasing rendering of the original input.

The three layers

The markup language we shall discuss comes in three layers: \TeX , \LaTeX , and the AMS packages, described in detail in Appendix D. Most \LaTeX installations—including the two covered in Appendix A—automatically place all three on your computer. You do not have to know what comes from which layer, so we consider the three together and call it \LaTeX .

The three platforms

Most of you run \LaTeX on one of the following three computer types:

- A PC, a computer running Microsoft Windows
- A Mac¹, a Macintosh computer running OS X
- A computer running a UNIX variant such as Solaris or Linux

The \LaTeX source file and the typeset version both look the same independent of what computer you have. However, the way you type your source file, the way you typeset it, and the way you look at the typeset version depends on the computer and on the \LaTeX implementation you use. In Appendix A, we show you how to install \LaTeX for a PC and a Mac. Many UNIX systems come with \LaTeX installed.

¹In the old days, I used to run `TEXTURES` under OS 9. Unfortunately, `TEXTURES` does not run on new Intel Macs.

What's in the book?

Part I is the *Short Course*; it helps you to get started quickly with L^AT_EX, to type your first articles, to prepare your first presentations, and it prepares you to tackle L^AT_EX in more depth in the subsequent parts. We assume here that L^AT_EX is installed on your computer. If it is not, jump to Appendix A.

Chapter 1 introduces the *terminology* we need to talk about your L^AT_EX implementations. **Chapter 2** introduces how L^AT_EX uses the *keyboard* and how to *type text*. You do not need to learn much to understand the basics. Text markup is quite easy. You learn math markup—which is not so straightforward—in **Chapter 3**. Several sections in this chapter ease you into *mathematical typesetting*. There is a section on the basic building blocks of math formulas. Another one discusses equations. Finally, we present the two simplest multiline formulas, which, however, cover most of your everyday needs.

In **Chapter 4**, you start writing your *first article* and prepare your *first presentation*. A L^AT_EX article is introduced with the sample article `intrart.tex`. We analyze in detail its structure and its source file, and we look at the typeset version. Based on this, we prepare an article template, and you are ready for your first article. A quick conversion of the article `intrart.tex` to a presentation introduces this important topic.

Part II introduces the two most basic skills for writing with L^AT_EX in depth, *typing text* and *typing math*.

Chapters 5 and 6 introduce *text* and *displayed text*. Chapter 5 is especially important because, when you type a L^AT_EX document, most of your time is spent typing text. The topics covered include special characters and accents, hyphenation, fonts, and spacing. Chapter 6 covers displayed text, including *lists* and *tables*, and for the mathematician, *proclamations* (theorem-like structures) and *proofs*.

Typing math is the heart of any mathematical typesetting system. **Chapter 7** discusses inline formulas in detail, including basic constructs, delimiters, operators, math accents, and horizontally stretchable lines. The chapter concludes with the *Formula Gallery*.

Math symbols are covered in three sections in **Chapter 8**. How to space them, how to build new ones. We also look at the closely related subjects of math alphabets and fonts. Then we discuss tagging and grouping equations.

L^AT_EX knows a lot about typesetting an inline formula, but not much about how to display a multiline formula. **Chapter 9** presents the numerous tools L^AT_EX offers to help you do that. We start with a *Visual Guide* to help you get oriented.

Part III discusses the parts of a L^AT_EX document. In **Chapter 10**, you learn about the *structure* of a L^AT_EX document. The most important topics are *sectioning* and *cross-referencing*. In **Chapter 11**, we discuss the `amsart` *document class* for articles. In particular, I present the title page information. Chapter 11 also features `sampart.tex`, a sample article for `amsart`, first in typeset form, then in mixed form, juxtaposing the source file and the typeset article. You can learn a lot about L^AT_EX just by reading the source file one paragraph at a time and seeing how that paragraph is typeset. We con-

clude this chapter with a brief description of the AMS distribution, the packages and document classes, of which `amsart` is a part.

In **Chapter 12** the most commonly used *legacy document classes* are presented, `article`, `report`, and `letter` (the book class is discussed in Chapter 18), along with a description of the standard L^AT_EX distribution. Although `article` is not as sophisticated as `amsart`, it is commonly used for articles not meant for publication.

In **Part IV**, we start with **Chapter 13**, discussing PDF files, *hyperlinks*, and the `hyperref` package. This prepares you for *presentations*, which are PDF files with hyperlinks. In **Chapter 14** we utilize the *beamer package* for making L^AT_EX presentations.

Part V (Chapter 15) introduces techniques to *customize L^AT_EX*: user-defined commands, user-defined environments, and command files. We present a sample command file, `newlattice.sty`, and a version of the sample article utilizing this command file. You learn how parameters that affect L^AT_EX's behavior are stored in counters and length commands, how to change them, and how to design your own custom lists. A final section discusses the pitfalls of customization.

In **Part VI (Chapters 16 and 17)**, we discuss the special needs of longer documents. Two applications, contained in the standard L^AT_EX distribution, `BIBTEX` and `MakeIndex`, make compiling *large bibliographies* and *indexes* much easier.

L^AT_EX provides the `book` and the `amsbook` document classes to serve as foundations for well-designed books. We discuss these in **Chapter 18**. Better quality books have to use document classes designed by professionals. We provide some sample pages from a book using Springer's `svmono.cls` document class.

Detailed instructions are given in **Appendix A** on how to install L^AT_EX on a PC and a Mac. On a PC we install WinEdt and MiKTeX. On a Mac, we install MacTeX, which consists of T_EX Live and TeXShop. For both installations, we describe the editing cycle and three productivity tools in sufficient detail so that you be able to handle the tasks on the sample files of the *Short Course*.

You will probably find yourself referring to **Appendices B** and **C** time and again. They contain the *math and text symbol tables*.

Appendix D relates some historical background material on L^AT_EX. It gives you some insight into how L^AT_EX developed and how it works. **Appendix E** discusses the many ways we can find L^AT_EX material on the *Internet*.

Appendix F is a brief introduction to the use of *PostScript fonts* in a L^AT_EX document. **Appendix G** briefly describes the use of L^AT_EX for languages other than American English.

Finally, **Appendix H** discusses what we left out and points you towards some areas for further reading.

Mission statement

This book is a guide for typesetting mathematical documents within the constraints imposed by L^AT_EX, an elaborate system with hundreds of rules. L^AT_EX allows you to perform almost any mathematical typesetting task through the appropriate application of its rules. You can customize L^AT_EX by introducing user-defined commands and environments and by changing L^AT_EX parameters. You can also extend L^AT_EX by invoking packages that accomplish special tasks.

It is *not my goal*

- to survey the hundreds of L^AT_EX packages you can utilize to enhance L^AT_EX
- to teach how to write T_EX code and to create your own packages
- to discuss how to design beautiful documents by writing document classes

The definitive book on the first topic is Frank Mittelbach and Michel Goossens's *The L^AT_EX Companion*, 2nd edition [46] (with Johannes Braams, David Carlisle, and Chris Rowley). The second and third topics still await authoritative treatment.

Conventions

To make this book easy to read, I use some simple conventions:

- Explanatory text is set in this typeface: Times.
- Computer Modern typewriter is used to show what you should type, as well as messages from LaTeX. All the characters in this typeface have the same width, making it easy to recognize.
- I also use Computer Modern typewriter to indicate
 - Commands (`\parbox`)
 - Environments (`\align`)
 - Documents (`intrart.tex`)
 - Document classes (`amsart`)
 - Document class options (`draft`)
 - Folders or directories (`work`)
 - The names of *packages*, which are extensions of L^AT_EX (`verbatim`)
- When I show you how something looks when typeset, I use Computer Modern, T_EX's standard typeface:

I think you find this typeface sufficiently different from the other typefaces I have used. The strokes are much lighter so that you should not have much difficulty recognizing typeset L^AT_EX material. When the typeset material is a separate paragraph or paragraphs, corner brackets in the margin set it off from the rest of the text—unless it is a displayed formula.

- For explanations in the text, such as

Compare `iff` with `iff`, typed as `iff` and `if{f}`, respectively.

the same typefaces are used. Because they are not set off spatially, it may be a little more difficult to see that `iff` is set in Computer Modern roman (in Times, it looks like this: `iff`), whereas `iff` is set in the Computer Modern typewriter typeface.

- I usually introduce commands with examples, such as

`\\[22pt]`

However, it is sometimes necessary to define the syntax of a command more formally. For instance,

`\\[length]`

where *length*, typeset in Computer Modern typewriter italic font, represents the value you have to supply.

Good luck and have fun.

George Gratzer

E-mail:

`gratzer@ms.umanitoba.ca`

Home page:

`http://www.maths.umanitoba.ca/homepages/gratzer.html`

PART I

Short Course

Your L^AT_EX

Are you sitting in front of your computer, your L^AT_EX implementation up and running? In this chapter we get you ready to tackle this *Short Course*. When you are done with Part I, you will be ready to start writing your articles in L^AT_EX.

If you do not have a L^AT_EX implementation up and running, go to Appendix A. There you find precise and detailed instructions how to set up L^AT_EX on a PC or a Mac. There is enough in the appendix for you to be able to handle the tasks in this *Short Course*. You will be pleasantly surprised at how little time it takes to set L^AT_EX up. If you use some variant of UNIX, turn to a UNIX guru who can help you set up L^AT_EX on your computer and guide you through the basics. If all else fails, read the documentation for your UNIX system.

1.1 Your computer

We assume very little, only that you are familiar with your keyboard and with the operating system on your computer. You should know standard PC and Mac menus, pull down menus, buttons, tabs, the menu items, such as Edit>Paste, the menu item Paste on the menu Edit. You should understand folders (we use this terminology regardless of the platform, with apologies to our UNIX readers), and you need to know how to save a file and copy a file from one folder to another.

On a PC, `work\test` refers to the subfolder `test` of the folder `work`. On a Mac, `work/test` designates this subfolder. To avoid having to write every subfolder twice, we use `work/test`, with apologies to our PC readers.

1.2 Sample files

We work with a few sample documents in this *Short Course*. You can type the sample documents as presented in the text, or you can download them from the Internet (see Section E.1). The `samples` folder also contains a copy of `SymbolTables.pdf`, a PDF version of Appendices B and C, the symbol tables.

I suggest you create a folder on your computer named `samples`, to store the downloaded sample files, and another folder called `work`, where you will keep your working files. Copy the documents from the `samples` to the `work` folder as needed. *In this book, the `samples` and `work` folders refer to the folders you have created.*

If you Save As . . . a sample file under a different name, remember the naming rule.

Rule ■ Naming of source files

The name of a L^AT_EX source file should be *one word* (no spaces, no special characters), and end with `.tex`.

So first `art.tex` is bad, but `art1.tex` and `FirstArt.tex` are good.

1.3 Editing cycle

Watch a friend type a mathematical article in L^AT_EX and you learn some basic steps.

1. A text editor is used to create a L^AT_EX source file. A source file might look like the top window in Figure 1.1:

```
\documentclass{amsart}
\begin{document}
The hypotenuse:  $\sqrt{a^2 + b^2}$ $. I can type math!
\end{document}
```

Note that the source file is different from a typical word processor file. All characters are displayed in the same font and size.

2. Your friend “typesets” the source file (tells the application to produce a typeset version) and views the result on the monitor (the two corners indicate material typeset by L^AT_EX):

```
┌
└   The hypotenuse:  $\sqrt{a^2 + b^2}$ . I can type math!
```

as in the middle window in Figure 1.1.

3. *The editing cycle continues.* Your friend goes back and forth between the source file and the typeset version, making changes and observing the results of these changes.
4. *The file is printed.* Once the typeset version is satisfactory, it is printed, creating a paper version of the typeset article. Alternatively, your friend creates a PDF file of the typeset version (see Chapter 13.1.2).

If L^AT_EX finds a mistake when typesetting the source file, it opens a new window, the *log window*, illustrated as the bottom window in Figure 1.1, and displays an error message. The same message is saved into a file, called the *log file*. Look at the figures in Appendix A, depicting a variety of editing windows, windows for the typeset article, and log windows for the two L^AT_EX implementations discussed there.

Various L^AT_EX implementations have different names for the source file, the text editor, the typeset file, the typeset window, the log window, and the log file. Become familiar with these names for the L^AT_EX implementation you use, so you can follow along with our discussions. In Appendix A, we bring you up to speed for the L^AT_EX implementations discussed therein.

1.4 Three productivity tools

Most L^AT_EX implementations have these important productivity tools:

Synchronization To move quickly between the source file and the typeset file, most L^AT_EX implementations offer *synchronization*, the ability to jump from the typeset




Figure 1.1: Windows for the source and typeset files and the log window.

file to the corresponding place in the source file and from the source file to the corresponding place in the typeset file.

Block comment Block comments are very useful:

1. When looking for a L^AT_EX error, you may want L^AT_EX to ignore a block of text in the source file (see page 51).
2. Often you may want to make comments about your project but not have them printed or you may want to keep text on hand while you try a different option. To accomplish this, insert a comment character, %, at the start of each line where the text appears. These lines are ignored when the L^AT_EX file is processed.

Select a number of lines in a source document, then by choosing a menu option all the lines (the whole block) are commented out (a % sign is placed at the beginning of each line). This is *block comment*. The reverse is *block uncomment*.

Jump to a line This is specified by the line number in the source file. To find an error, L^AT_EX suggests that you jump to a line.

Find out how your L^AT_EX implements these features. In Appendix A, we discuss how these features are implemented for the L^AT_EX we install.

Pay careful attention how your L^AT_EX implementation works. This enables you to rapidly perform the editing cycle and utilize the productivity tools when necessary.

Typing text

In this chapter, I introduce you to typesetting text by working through examples. More details are provided throughout the book, in particular, in Chapters 5 and 6.

A source file is made up of *text*, *math (formulas)*, and *instructions (commands) to L^AT_EX*. For instance, consider the following variant of the first sentence of this paragraph:

```
A source file is made up of text, math (e.g.,
 $\sqrt{5}$ ), and \emph{instructions to} \LaTeX.
```

This typesets as

```
┌
| A source file is made up of text, math (e.g.,  $\sqrt{5}$ ), and instructions to LATEX.
└
```

In this sentence, the first part

```
A source file is made up of text, math (e.g.,
```

is text. Then

```
 $\sqrt{5}$ 
```

is math

), and

is text again. Finally,

```
\emph{instructions to} \LaTeX.
```

are instructions. The instruction `\emph` is a *command with an argument*, while the instruction `\LaTeX` is a *command without an argument*.

Commands, as a rule, start with a backslash (`\`) and tell \LaTeX to do something special. In this case, the command `\emph` emphasizes its *argument* (the text between the braces). Another kind of instruction to \LaTeX is called an *environment*. For instance, the commands

```
\begin{flushright}
```

and

```
\end{flushright}
```

enclose a `flushright` environment; the *content*, that is, the text that is typed between these two commands, is right justified (lined up against the right margin) when typeset. (The `flushleft` environment creates left justified text; the `center` environment creates text that is centered horizontally on the page.)

In practice, text, math, and instructions (commands) are mixed. For example,

```
My first integral: $\int \zeta^2(x) \, dx$.
```

is a mixture of all three; it typesets as

```
┌
└ My first integral:  $\int \zeta^2(x) dx$ .
```

Creating a document in \LaTeX requires that we type the text and math in the source file. So we start with the keyboard, proceed to type a short note, and learn some simple rules for typing text in \LaTeX .

2.1 The keyboard

The following keys are used to type text in a source file:

```
a-z  A-Z  0-9
+ = * / ( ) [ ]
```

You may also use the following punctuation marks:

, ; . ? ! : ‘ ’ -

and the space bar, the Tab key, and the Return (or Enter) key.

Since \TeX source files are “pure text” (ASCII files), they are very portable. There is one possible problem limiting this portability, the line endings used in the source file. When you press the Return key, your text editor writes an invisible code into your source file that indicates where the line ends. Since this code may be different on different platforms (PC, Mac, and UNIX), you may have problems reading a source file created on a different platform. Luckily, many text editors include the ability to switch end-of-line codes and some, including the editors in WinEdt and TeXShop, do so automatically.

Finally, there are thirteen special keys that are mostly used in \LaTeX commands:

\$ % & ~ _ ^ \ { } @ " |

If you need to have these characters typeset in your document, there are commands to produce them. For instance, \$ is typed as `\$`, the underscore, `_`, is typed as `_`, and % is typed as `\%`. Only @ requires no special command, type @ to print @. There are also commands to produce composite characters, such as accented characters, for example ä, which is typed as `\"a`. See Section 5.4.4 for a complete discussion of symbols not available directly from the keyboard and Appendix C for the text symbol tables. Appendices B and C are reproduced in the `samples` folder as a PDF file, `SymbolTables.pdf`.

\LaTeX prohibits the use of other keys on your keyboard—unless you are using a version of \LaTeX that is set up to work with non-English languages (see Appendix G). When trying to typeset a source file that contains a prohibited character, \LaTeX displays an error message similar to the following:

```
! Text line contains an invalid character.
1.222 completely irreducible^^?
                ^^?
```

In this message, 1.222 means line 222 of your source file. You must edit that line to remove the character that \LaTeX cannot understand. The log file (see Section D.3.4) also contains this message. For more about \LaTeX error messages, see Sections 3.2 and 4.3.1.

2.2 *Your first note*

We start our discussion on how to type a note in \LaTeX with a simple example. Suppose you want to use \LaTeX to produce the following:

It is of some concern to me that the terminology used in multi-section math courses is not uniform.

In several sections of the course on matrix theory, the term “hamiltonian-reduced” is used. I, personally, would rather call these “hyper-simple”. I invite others to comment on this problem.

Of special concern to me is the terminology in the course by Prof. Rudi Hochschwabauer. Since his field is new, there is no accepted terminology. It is imperative that we arrive at a satisfactory solution.

To produce this typeset document, create a new file in your work folder with the name `note1.tex`. Type the following, including the spacing and linebreaks shown, but not the line numbers:

```

1  % Sample file: note1.tex
2  \documentclass{sample}
3
4  \begin{document}
5  It is of some concern to me that
6  the terminology used in multi-section
7  math courses is not uniform.
8
9  In several sections of the course on
10 matrix theory, the term
11 ‘‘hamiltonian-reduced’’ is used.
12 I, personally, would rather call these
13 ‘‘hyper-simple’’. I invite others
14 to comment on this problem.
15
16 Of special concern to me is the terminology
17 in the course by Prof. Rudi Hochschwabauer.
18 Since his field is new, there is no accepted
19 terminology. It is imperative
20 that we arrive at a satisfactory solution.
21 \end{document}

```

Alternatively, copy the `note1.tex` file from the samples folder (see page 4). Make sure that `sample.cls` is in your work folder.

The first line of `note1.tex` starts with `%`. Such lines are called *comments* and are ignored by \LaTeX . Commenting is very useful. For example, if you want to add some notes to your source file and you do not want those notes to appear in the typeset version of your article, you can begin those lines with a `%`. You can also comment out part of a line:

simply put, we believe % actually, it's not so simple

Everything on the line after the % character is ignored by L^AT_EX.

Line 2 specifies the *document class* (in our case, `sample`)¹ that controls how the document is formatted.

The text of the note is typed within the `document` environment, that is, between the lines

```
\begin{document}
```

and

```
\end{document}
```

Now typeset `note1.tex`. If you use WinEdt, click on the TeXify icon. If you use TeXShop, click the Typeset button. You should get the typeset document as shown on page 10. As you can see from this example, L^AT_EX is different from a word processor. It disregards the way you input and position the text, and follows only the formatting instructions given by the markup commands. L^AT_EX notices when you put a blank space in the text, but it ignores *how many blank spaces* have been inserted. L^AT_EX does not distinguish between a blank space (hitting the space bar), a tab (hitting the Tab key), and a *single* carriage return (hitting Return once). However, hitting Return twice gives a blank line; *one or more* blank lines mark the end of a paragraph.

L^AT_EX, by default, fully justifies text by placing a flexible amount of space between words—the *interword space*—and a somewhat larger space between sentences—the *intersentence space*. If you have to force an interword space, you can use the `_` command (in L^AT_EX books, we use the symbol `_` to mean a blank space). See Section 5.2.2 for a full discussion.

The `~` (tilde) command also forces an interword space, but with a difference; it keeps the words on the same line. This command is called a *tie* or *nonbreakable space* (see Section 5.4.3).

Note that on lines 11 and 13, the left double quotes are typed as ‘ ‘ (two left single quotes) and the right double quotes are typed as ’ ’ (two right single quotes or apostrophes). The left single quote key is not always easy to find. On an American keyboard,² it is usually hidden in the upper-left or upper-right corner of the keyboard, and shares a key with the tilde (`~`).

¹I know you have never heard of the `sample` document class. It is a special class created for these exercises. You can find it in the `samples` folder (see page 4). If you have not yet copied it over to the `work` folder, do so now.

²The location of special keys on the keyboard depends on the country where the computer was sold. It also depends on whether the computer is a PC or a Mac. In addition, notebooks tend to have fewer keys than desktop computers. Fun assignment: Find the tilde (`~`) on a Spanish and on a Hungarian keyboard.

2.3 Lines too wide

\LaTeX reads the text in the source file one line at a time and when the end of a paragraph is reached, \LaTeX typesets the entire paragraph. Occasionally, \LaTeX gets into trouble when trying to split the paragraph into typeset lines. To illustrate this situation, modify `note1.tex`. In the second sentence, replace `term` by `strange term` and in the fourth sentence, delete `Rudi`, including the blank space following `Rudi`. Now save this modified file in your work folder using the name `note1b.tex`. You can also find `note1b.tex` in the `samples` folder (see page 4).

Typesetting `note1b.tex`, you obtain the following:

It is of some concern to me that the terminology used in multi-section math courses is not uniform.

In several sections of the course on matrix theory, the strange term “hamiltonian-reduced” is used. I, personally, would rather call these “hyper-simple”. I invite others to comment on this problem.

Of special concern to me is the terminology in the course by Prof. Hochschwabauer. Since his field is new, there is no accepted terminology. It is imperative that we arrive at a satisfactory solution.

The first line of paragraph two is about 1/4 inch too wide. The first line of paragraph three is even wider. In the log window, \LaTeX displays the following messages:

```
Overfull \hbox (15.38948pt
too wide) in paragraph at lines 9--15 []\OT1/cmr/m/n/10 In sev-eral
sec-tions of the course on ma-trix the-ory, the strange term
‘‘hamiltonian-
```

```
Overfull \hbox (23.27834pt too wide) in paragraph
at lines 16--21
[]\OT1/cmr/m/n/10 Of spe-cial con-cern to me is the
ter-mi-nol-ogy in the course by Prof. Hochschwabauer.
```

You will find the same messages in the log file (see Sections 1.3 and D.2.1).

The first message,

```
Overfull \hbox (15.38948pt too wide) in paragraph
at lines 9--15
```

refers to the second paragraph (lines 9–15 in the source file—its location in the typeset document is not specified). The typeset version of this paragraph has a line that is 15.38948 points too wide. \LaTeX uses *points* (pt) to measure distances; there are about 72 points in 1 inch (or about 28 points in 1 cm).

The next two lines,

```
[]\OT1/cmr/m/n/10 In sev-eral sec-tions of the course
on ma-trix
the-ory, the strange term ‘‘hamiltonian-
identify the source of the problem: LATEX did not properly hyphenate the word
hamiltonian-reduced
```

because it (automatically) hyphenates a hyphenated word *only at the hyphen*.

The second reference,

```
Overfull \hbox (23.27834pt too wide) in paragraph
at lines 16--21
```

is to the third paragraph (lines 16–21 of the source file). There is a problem with the word Hochschwabauer; L^AT_EX’s standard hyphenation routine cannot handle it (a German hyphenation routine would have no difficulty hyphenating this name—see Appendix G). If you encounter such a problem, you can either try to reword the sentence or insert one or more *optional (or discretionary) hyphen commands* (\-), which tell L^AT_EX where it may hyphenate the word. In this case, you can rewrite Hochschwabauer as Hoch\-schwa\-bauer and the second hyphenation problem disappears. You can also utilize the \hyphenation command (see Section 5.4.9).

Sometimes a small horizontal overflow can be difficult to spot. The draft document class option may help (see Sections 11.5, 12.1.2, and 18.1 for more about document class options). L^AT_EX places a black box (or *slug*) in the margin to mark an overfull line. You can invoke this option by changing the \documentclass line to

```
\documentclass[draft]{sample}
```

A version of note1b.tex with this option can be found in the samples folder under the name noteslug.tex. Typeset it to see the “slugs”.

2.4 More text features

Next, we produce the following note:

┌

September 12, 2006

From the desk of George Grätzer

October 7–21 *please* use my temporary e-mail address:

George.Gratzer@yahoo.com

└

Type in the source file, without the line numbers. Save it as `note2.tex` in your work folder (`note2.tex` can be found in the `samples` folder—see page 4):

```

1  % Sample file: note2.tex
2  \documentclass{sample}
3
4  \begin{document}
5  \begin{flushright}
6    \today
7  \end{flushright}
8  \textbf{From the desk of George Gr\{a}tzer}\[22pt]
9  October~7--21 \emph{please} use my
10 temporary e-mail address:
11 \begin{center}
12   \texttt{George\_Gratzer@yahoo.com}
13 \end{center}
14 \end{document}

```

This note introduces several additional text features of L^AT_EX:

- The `\today` command (in line 6) to display the date on which the document is typeset (so you will see a date different from the date shown above in your own typeset document).
- The environments to *right justify* (lines 5–7) and *center* (lines 11–13) text.
- The commands to change the text style, including the `\emph` command (line 8) to *emphasize* text, the `\textbf` command (line 9) for **bold** text, and the `\texttt` command (line 12) to produce *typewriter* style text.

These are *commands with arguments*. In each case, the argument of the command follows the name of the command and is typed between braces, that is, between `{` and `}`.

- The form of the L^AT_EX commands: Almost all L^AT_EX *commands* start with a backslash (`\`) followed by the *command name*. For instance, `\textbf` is a command and `textbf` is the command name. The command name is terminated by the first *non-alphabetic character*, that is, by any character other than a–z or A–Z. So `textbf1` is not a command name, in fact, `\textbf1` typesets as **1**. (Let us look at this a bit more closely. `\textbf` is a valid command. If a command needs an argument and is not followed by braces, then it takes the next character as its argument. So `\textbf1` is the command `\textbf` with the argument `1`, which typesets as bold 1: **1**.) Note that command names are *case sensitive*. Typing `\Textbf` or `\TEXTBF` generates an error message.
- The multiple role of hyphens: Double hyphens are used for number ranges. For example, `7--21` (in line 9) typesets as 7–21. The punctuation mark – is called an *en*

dash. Use triple hyphens for the *em dash* punctuation mark—such as the one in this sentence.

- The *new line* command, `\\` (or `\newline`): To create additional space between lines (as in the last note, under the line **From the desk...**), you can use the `\\` command and specify an appropriate amount of vertical space: `\\[22pt]`. Note that this command uses *square brackets* rather than braces because the argument is *optional*. The distance may be given in points (`pt`), centimeters (`cm`), or inches (`in`). (There is an analogous *new page* command, `\newpage`, not used in this short note.)
- Special rules for special characters (see Section 2.1), for *accented characters* and for some *European characters*. For instance, the accented character ä is typed as `\"a`. Accents are explained in Section 5.4.7 (see also the tables in Section C.2).

When you need to know more about typing text than we have discussed here, see Chapters 5 and 6. See also Appendix C, where all text symbols are organized into tables. Recall that we also have the `SymbolTables.pdf` in the `samples` folder.

Typing math

While marking up text in \LaTeX is easy, marking up math is less intuitive because math formulas are two-dimensional constructs and we have to mark them up with a one-dimensional string of characters. However, even the most complicated two-dimensional formula is made up of fairly simple building blocks. So by concentrating on the building blocks—selectively, just learn the ones you need—you can get started with math quickly.

3.1 *A note with math*

In addition to the regular text keys and the 13 special keys discussed in Section 2.1, two more keys are used to type math:

$$< >$$

The formula $2 < |x| > y$ (typed as $\$2 < |x| > y\$$) uses both. Note that such math formulas, called *inline*, are enclosed by $\$$ symbols. We discuss shortly another kind of math formula called *displayed*.

We begin typesetting math with the following note:

In first-year calculus, we define intervals such as (u, v) and (u, ∞) . Such an interval is a *neighborhood* of a if a is in the interval. Students should realize that ∞ is only a symbol, not a number. This is important since we soon introduce concepts such as $\lim_{x \rightarrow \infty} f(x)$.

When we introduce the derivative

$$\lim_{x \rightarrow a} \frac{f(x) - f(a)}{x - a},$$

we assume that the function is defined and continuous in a neighborhood of a .

To create the source file for this mixed text and math note, create a new document with your text editor. Name it `math.tex`, place it in the `work` folder, and type in the following source file—without the line numbers—or simply copy `math.tex` from the `samples` folder (see page 4):

```

1 % Sample file: math.tex
2 \documentclass{sample}
3
4 \begin{document}
5 In first-year calculus, we define intervals such
6 as  $(u, v)$  and  $(u, \infty)$ . Such an interval
7 is a neighborhood of  $a$ 
8 if  $a$  is in the interval. Students should
9 realize that  $\infty$  is only a
10 symbol, not a number. This is important since
11 we soon introduce concepts
12 such as  $\lim_{x \rightarrow \infty} f(x)$ .
13
14 When we introduce the derivative
15 \[
16 \lim_{x \rightarrow a} \frac{f(x) - f(a)}{x - a},
17 \]
18 we assume that the function is defined and
19 continuous in a neighborhood of  $a$ .
20 \end{document}

```

This note introduces several basic concepts of math in \LaTeX :

- There are two kinds of math formulas and environments in `math.tex`:
 - *Inline* math environments open and close with `$` (as seen throughout this book) or open with `\(` and close with `\)`.
 - *Displayed* math environments open with `\[` and close with `\]`.

- Within math environments, \LaTeX uses its own spacing rules and completely ignores the white space you type, with two exceptions:
 - Spaces that terminate commands. So in $\$\infty a\$$ the space is not ignored, $\$\infty a\$$ produces an error.
 - Spaces in the arguments of commands that temporarily revert to regular text. $\text{\texttt{\textbackslash text}}$ is such a command (see Sections 3.3 and 7.4.6).

The white space that you add when typing math is important only for the readability of the source file. We summarize with a simple rule.

Rule ■ Spacing in text and math

Many spaces equal one space in text, whereas your spacing is ignored in math, unless the space terminates a command.

- A math symbol is invoked by a command. For example, the command for ∞ is $\text{\texttt{\textbackslash infinity}}$ and the command for \rightarrow is $\text{\texttt{\textbackslash to}}$. The math symbols are organized into tables in Appendix B (see also `SymbolTables.pdf` in the `samples` folder).
- Some commands, such as $\text{\texttt{\textbackslash sqrt}}$, need *arguments* enclosed by $\{$ and $\}$. To typeset $\sqrt{5}$, type $\$\text{\texttt{\textbackslash sqrt}}\{5}\$$, where $\text{\texttt{\textbackslash sqrt}}$ is the command and 5 is the argument. Some commands need more than one argument. To get

$$\frac{3+x}{5}$$

type

```
\[
  \frac{3+x}{5}
\]
```

where $\text{\texttt{\textbackslash frac}}$ is the command, $3+x$ and 5 are the arguments—we indent for readability.

3.2 Errors in math

Even in such a simple note there are opportunities for errors. To help familiarize yourself with some of the most commonly seen \LaTeX math errors and their causes, we deliberately introduce mistakes into `math.tex`. The version of `math.tex` with mistakes is `mathb.tex`. By inserting and deleting $\%$ signs, you make the mistakes visible to \LaTeX one at a time—recall that lines starting with $\%$ are comments and are therefore ignored by \LaTeX .

Type the following source file, and save it under the name `mathb.tex` in the work folder or copy the file `mathb.tex` from the `samples` folder (see page 4). Do not type the line numbers—they are shown here to help you with the experiments.

```

1 % Sample file: mathb.tex
2 \documentclass{sample}
3
4 \begin{document}
5 In first-year calculus, we define intervals such
6 % as  $(u, v)$  and  $(u, \infty)$ . Such an interval
7 as  $(u, v)$  and  $(u, \infty)$ . Such an interval
8 is a \emph{neighborhood} of  $a$ 
9 if  $a$  is in the interval. Students should
10 realize that  $\infty$  is only a
11 symbol, not a number. This is important since
12 we soon introduce concepts
13 such as  $\lim_{x \to \infty} f(x)$ .
14 %such as  $\lim_{x \to \infty} f(x)$ .
15
16 When we introduce the derivative
17 \[
18 \lim_{x \to a} \frac{f(x) - f(a)}{x - a}
19 % \lim_{x \to a} \frac{f(x) - f(a)}{x - a}
20 \]
21 we assume that the function is defined and
22 continuous in a neighborhood of  $a$ .
23 \end{document}

```

Experiment 1 In line 7, the `$` before the `(u` is missing. Typeset the `mathb.tex` source file. \LaTeX generates the following error message:

```

! Missing $ inserted.
<inserted text>
$
1.7 as  $(u, v)$  and  $(u, \infty$ 
                                 $)$ . Such an interval

```

Since the `$` was omitted, \LaTeX reads `(u, \infty)` as text; but the `\infty` command instructs \LaTeX to typeset a math symbol, which can only be done in a math formula. So \LaTeX offers to put a `$` in front of `\infty` while typesetting the source file—it does not put the `$` in the source file itself. \LaTeX attempts a cure, but in this example it comes too late, because the math formula *should* start just before `(u`.

Whenever you see the ? prompt, you may press Return to ignore the error and continue typesetting the document. Section D.4 lists a number of other options and prompts.

Experiment 2 Uncomment line 6 by deleting the % at the beginning of line 6 and comment out line 7 by inserting a % at the beginning of line 7. This eliminates the previous error. Uncomment line 14 and comment out line 13. This introduces a new error, the closing brace of the subscript is missing. Now typeset the note. You get the error message

```
! Missing } inserted.
<inserted text>
      }
1.14 such as  $\lim_{x \to \infty} f(x)$ 
```

\LaTeX reports that a closing brace (}) is missing, but it is not sure where the brace should be. \LaTeX noticed that a subscript (see page 23) started with {, but \LaTeX reached the end of the math formula before finding a closing brace }. To remedy this, you must look in the formula for an opening brace { that is not balanced, and insert the missing closing brace }. Make the necessary change and typeset again to view the difference.

Experiment 3 Uncomment line 13 and comment out line 14, removing the previous error. Delete the % at the beginning of line 19 and insert a % at the beginning of line 18, introducing our final error, omitting the closing brace of the first argument and the opening brace of the second argument of `\frac`. Save and typeset the file. You get the error message

```
! Too many }'s.
\frac #1#2->{\beginngroup #1\endgroup \@@over #2}
1.20 \]
```

\LaTeX got confused. The second line of the message explains that `\frac` has two arguments and it is not working out, but the error is incorrectly identified.

If the typo on line 19 is `\frac{f(x)-f(a) x-a}g`, then \LaTeX produces

$$\frac{f(x) - f(a)x - a}{g}$$

and no error message is generated.

Experiment 4 Make sure all the errors are commented out. Typeset `mathb.tex`, testing that there are no errors. Now delete the two \$ signs in line 22, that is, replace `a` by `a`. Typeset the file. It typesets with no errors. Here is the last line of the typeset file you get:

⌈
 we assume that the function is defined and continuous in a neighborhood of a .
 ⌋

instead of

⌈
 we assume that the function is defined and continuous in a neighborhood of a .
 ⌋

This is probably the error most often made by beginners. There is no error message by \LaTeX and the typeset version looks good. You need sharp eyes to catch such an error.

See Section 4.3.1 for more information about finding and fixing problems in your \LaTeX source files.

3.3 *Building blocks of a formula*

A formula is built from a large collection of components. We group them as follows:

- Arithmetic
 - Subscripts and superscripts
- Binomial coefficients
- Congruences
- Delimiters
- Ellipses
- Integrals
- Math accents
- Matrices
- Operators
 - Large operators
- Roots
- Text

In this section, I describe each of these groups, and provide examples illustrating their use.

Arithmetic The arithmetic operations $a + b$, $a - b$, $-a$, a/b , and ab are typed in the natural way (the spaces are typed only for readability, others may type fewer spaces):

`$a + b$`, `$a - b$`, `$-a$`, `a / b`, `$a b$`

If you wish to use \cdot or \times for multiplication, as in $a \cdot b$ or $a \times b$, use `\cdot` or `\times`, respectively. The expressions $a \cdot b$ and $a \times b$ are typed as follows:

`$a \cdot b$` `$a \times b$`

Displayed fractions, such as

$$\frac{1 + 2x}{x + y + xy}$$

are typed with `\frac`:

```
\[
\frac{1 + 2x}{x + y + xy}
\]
```

The `\frac` command is seldom used inline because it can disrupt the interline spacing of the paragraph.

Subscripts and superscripts Subscripts are typed with `_` (underscore) and superscripts with `^` (caret). Subscripts and superscripts should be enclosed in braces, that is, typed between `{` and `}`. To get a_1 , type `a_{1}`. Omitting the braces in this example causes no harm, but to get a_{10} , you *must* type `a_{10}`. Indeed, `a_10` is typeset as a_10 . Further examples, a_{i_1} , a^2 , a^{i_1} , a_n^2 , are typed as

`$a_{i_{1}}$`, `a^{2}`, `$a^{i_{1}}$`, `a_{n}^{2}`

There is one symbol, the prime (`'`), that is automatically superscripted in math. To get $f'(x)$, just type `$f'(x)$`.

Binomial coefficients Binomial coefficients are typeset with the `\binom` command.

For example, $\binom{a}{b+c}$ is typed inline as

`$\binom{a}{b + c}$`

whereas a displayed version,

$$\binom{\frac{n^2-1}{2}}{n+1}$$

is typed as

```
\[
\binom{\frac{n^2-1}{2}}{n+1}
\]
```

Congruences The two most important forms are

$$\begin{array}{ll} a \equiv v \pmod{\theta} & \text{typed as } \$a \equiv v \pmod{\theta}\$ \\ a \equiv v (\theta) & \text{typed as } \$a \equiv v \pmod{\theta}\$ \end{array}$$

Delimiters Parentheses and square brackets are examples of delimiters. They are used to delimit some subformulas, as in $[(a*b)+(c*d)]^2$, which typesets as $[(a * b) + (c * d)]^2$. \LaTeX can be instructed to expand them vertically to enclose a formula such as

$$\left(\frac{1+x}{2+y^2}\right)^2$$

which is typed as

```
\[
\left(\frac{1+x}{2+y^2}\right)^2
\]
```

The `\left(` and `\right)` commands tell \LaTeX to size the parentheses correctly, relative to the size of the symbols inside the parentheses. Two further examples,

$$\left|\frac{a+b}{2}\right|, \quad \|A^2\|$$

would be typed as

```
\[
\left|\frac{a+b}{2}\right|,
\quad \left\|A^2\right\|
\]
```

where `\quad` is a spacing command (see Sections 8.1 and B.9).

Additional delimiters are listed in Sections 7.5 and B.6.

Ellipses The *ellipsis* (...) in text is provided by the `\dots` command:

A...Z is typed as `A \dots Z`

In formulas, the ellipsis is printed either as *low* (or *on-the-line*) dots:

$F(x_1, \dots, x_n)$ is typed as `$F(x_{1}, \dots, x_{n})$`

or as centered dots:

$x_1 + \dots + x_n$ is typed as `$x_{1} + \dots + x_{n}$`

The command `\dots` typesets the correct ellipsis with the correct spacing in most cases. If it does not, see Section 7.4.3 on how to specify the appropriate ellipsis from the four types available.

Integrals The command for an integral is `\int`. The lower limit is specified as a subscript and the upper limit is specified as a superscript. For example, the formula $\int_0^\pi \sin x \, dx = 2$ is typed as

```
\int_{0}^{\pi} \sin x \, dx = 2
```

where `\,` is a spacing command (see Sections 8.1 and B.9).

Math accents The four most frequently used math accents are:

\bar{a} typed as `\bar{a}`

\hat{a} typed as `\hat{a}`

\tilde{a} typed as `\tilde{a}`

\vec{a} typed as `\vec{a}`

See Sections 7.7 and B.8 for complete lists.

Matrices You type the matrix

$$\begin{array}{cccc} a + b + c & uv & x - y & 27 \\ a + b & u + v & z & 134 \end{array}$$

with the `\matrix` command

```
\[
\begin{matrix}
a + b + c & & uv & & x - y & & 27 \\
a + b & & u + v & & z & & 134
\end{matrix}
\]
```

The `matrix` environment separates adjacent matrix elements within a row with ampersands (&). Rows are *separated* by new line commands (`\\`). Do not end the last row with a new line command!

The `matrix` environment has to appear within a math environment, as in the example. As a rule, it is in a displayed math environment, since inline it appears too large. It can be used in the `align` environment discussed in Section 3.4.2.

The `matrix` environment does not provide delimiters. Several variants do, including `pmatrix` and `vmatrix`. For example,

$$\mathbf{A} = \left(\begin{array}{cc} a + b + c & uv \\ a + b & u + v \end{array} \right) \left| \begin{array}{c} 30 \quad 7 \\ 3 \quad 17 \end{array} \right|$$

is typed as follows:

```

\[
\mathbf{A} =
\begin{pmatrix}
a + b + c & uv \\
a + b & u + v
\end{pmatrix}
\begin{vmatrix}
30 & 7 \\
3 & 17
\end{vmatrix}
\]

```

As you can see, `pmatrix` typesets as a matrix between a pair of `\left(` and `\right)` commands, while `vmatrix` typesets as a matrix between a pair of `\left|` and `\right|` commands. See Section 9.7.1 for a listing of all the matrix variants.

Operators To typeset the sine function, $\sin x$, type `\sin x`.

Note that `\sin x` would be typeset as $\sin x$ because \LaTeX interprets this expression as the product of four variables.

\LaTeX calls `\sin` an *operator*. Sections 7.6.1 and B.7 list a number of operators. See Section 7.6.2 for user-defined operators. Some are just like `\sin`. Others produce a more complex display, for example,

$$\lim_{x \rightarrow 0} f(x) = 0$$

is typed as

```

\[
\lim_{x \to 0} f(x) = 0
\]

```

Large operators The command for *sum* is `\sum` and for *product* is `\prod`. The following examples,

$$\sum_{i=1}^n x_i^2 \quad \prod_{i=1}^n x_i^2$$

are typed as

```

\[
\sum_{i=1}^n x_{i}^2 \quad \prod_{i=1}^n x_{i}^2
\]

```

where `\qquad` is a spacing command (see Sections 8.1 and B.9) used to separate the two formulas, yielding twice the space produced by `\quad`.

Sums and products are examples of *large operators*. They are typeset bigger when displayed than inline. They are listed in Sections 7.6.4 and B.7.1.

Roots `\sqrt` produces a square root. For instance, $\sqrt{a + 2b}$ is typed as

```
\sqrt{a + 2b}
```

The n -th root, $\sqrt[n]{5}$, requires the use of an *optional argument*, which is specified using brackets (see Section 5.3.1): `\sqrt[n]{5}`.

Text You can include text in a formula with a `\text` command. For instance,

$$a = b, \quad \text{by assumption}$$

is typed as

```
\[
  a = b, \text{\qquad by assumption}
\]
```

Note the spacing command `\qquad` in the argument of `\text`. You could also type

```
\[
  a = b, \qquad \text{by assumption}
\]
```

because `\qquad` works in math as well as in text (see Sections 8.1 and B.9).

3.4 Displayed formulas

3.4.1 Equations

The `equation` environment creates a displayed math formula and automatically generates an equation number. The equation

$$(1) \quad \int_0^\pi \sin x \, dx = 2$$

is typed as

```
\begin{equation}\label{E:firstInt}
  \int_0^\pi \sin x \, dx = 2
\end{equation}
```

The equation number, which is automatically generated, depends on how many other numbered equations occur before the given equation.

To reference this formula without having to remember a number—which may change when you edit your document—give the equation a symbolic label by using the `\label` command and refer to the equation in your document by using the symbolic label, the argument of the `\label` command. In this example, I have called the first equation `firstInt` (first integral), and used the convention that the label of an equation starts with `E:`, so that the complete `\label` command is

```
\label{E:firstInt}
```

The number of this formula is referenced with the `\ref` command. Its page is referenced using the `\pageref` command. For example, to get

```
[
see (1) on page 27
]
```

type

```
see~(\ref{E:firstInt}) on page~\pageref{E:firstInt}
```

The `\eqref` command provides the reference number in parentheses. So the last example could be typed

```
see~\eqref{E:firstInt} on page~\pageref{E:firstInt}
```

The `\eqref` command is smart. Even if the equation number is referenced in emphasized or italicized text, the reference typesets upright (in roman type).

Note the use of the nonbreakable space (`~`) to ensure that when typeset the equation number is on the same line as the word `see`. (See the footnote on page 11.) You should always use a nonbreakable space to link a `\ref` command to the name of its part, for instance, equation, page, section, chapter. Use two nonbreakable spaces in

```
Sections~\ref{S:main} and~\ref{S:subsidiary}.
```

The main advantage of this cross-referencing system is that when you add, delete, or rearrange equations, \LaTeX automatically renumbers the equations and adjusts the references that appear in your typeset document. You can split a long article into two or move a section to the end, and \LaTeX takes care of the renumbering. This significantly reduces the amount of time you need to spend working on your document. It also reduces the potential for errors in the finished project.

Rule ■ Typeset twice

For renumbering to work, you have to typeset the source file twice.

The first run creates a list of references that need to be linked. The second creates the cross references and inserts the relevant text throughout the document (see Sections 18.2 and D.3.4). \LaTeX issues a warning if you forget. Such warnings do not interrupt the typesetting, you only see them in the log window—if the window is visible—and in the log file. It is a good idea to check for warnings periodically.

An equation is numbered whether or not there is a `\label` command attached to it. Of course, if there is no `\label` command, the number generated for the equation by \LaTeX cannot be referenced with the command `\ref` or `\eqref`.

The system described here is called *symbolic referencing*. The symbol for the number is the argument of the `\label` command, and that symbol can be referenced with `\ref`, `\eqref`, or `\pageref` commands. \LaTeX uses the same mechanism for all of the generated numbering systems: sections, subsections, subsubsections, equations, theorems, lemmas, and bibliographic references—except that for bibliographic references, \LaTeX uses the `\bibitem` command to define a bibliographic item and the `\cite` command to cite a bibliographic item (see Section 4.2.4 and Chapter 16).

What happens if you misspell a reference, e.g., typing `\ref{E:firstint}` instead of `\ref{E:firstInt}`? \LaTeX typesets `??`. There are two warnings in the log file:

```
LaTeX Warning: Reference 'E:firstint' on page 39
                undefined on input line 475.
```

for the typeset page and the other one close to the end:

```
LaTeX Warning: There were undefined references.
```

If a `\cite` is misspelled, you get `[?]` and similar warnings.

Equations can also be *tagged* by attaching a name to the formula with the `\tag` command. The tag replaces the equation number.

For example,

$$(Int) \quad \int_0^{\pi} \sin x \, dx = 2$$

is typed as

```
\begin{equation}
  \int_0^{\pi} \sin x \, dx = 2 \tag{Int}
\end{equation}
```

Tags (of the type discussed here) are *absolute*. This equation is *always* referred to as (Int). Equation numbers, on the other hand, are *relative*, they may change when equations are added, deleted, or rearranged.

3.4.2 Aligned formulas

L^AT_EX has many ways to typeset multiline formulas. We discuss three constructs in this section: *simple alignment*, *annotated alignment*, and *cases*. See Chapter 9 for many others.

For simple and annotated alignment we use the `align` environment. Each line in the `align` environment is a separate equation, which L^AT_EX automatically numbers.

Simple alignment

Simple alignment is used to align two or more formulas. To obtain the formulas

$$\begin{aligned} (2) \quad & r^2 = s^2 + t^2, \\ (3) \quad & 2u + 1 = v + w^\alpha, \\ (4) \quad & x = \frac{y + z}{\sqrt{s + 2u}}; \end{aligned}$$

type the following, using `\\` as the *line separator* and `&` as the *alignment point*:

```
\begin{align}
r^{2} & \&= s^{2} + t^{2}, & \label{E:Pyth}\\
2u + 1 & \&= v + w^{\alpha}, & \label{E:alpha}\\
x & \&= \frac{y + z}{\sqrt{s + 2u}}; & \label{E:frac}
\end{align}
```

Note that you should not have a `\\` to terminate the last line.

Figure 3.1 displays the source and the typeset versions of formulas (2)–(4), emphasizing the alignment points of the source and the typeset formula. Of course, in the source, the alignment points do not have to line up.

These formulas are numbered (2), (3), and (4) because they are preceded by one numbered equation earlier in this section.

The `align` environment can also be used to break a long formula into two or more parts. Since numbering both lines in such a case would be undesirable, you can prevent the numbering of the second line by using the `\notag` command in the second part of the formula.

For example,

$$\begin{aligned} (5) \quad h(x) &= \int \left(\frac{f(x) + g(x)}{1 + f^2(x)} + \frac{1 + f(x)g(x)}{\sqrt{1 - \sin x}} \right) dx \\ &= \int \frac{1 + f(x)}{1 + g(x)} dx - 2 \tan^{-1}(x - 2) \end{aligned}$$

is typed as follows:

```
\begin{align}
h(x) & \&= \int \left( \frac{f(x) + g(x)}{1 + f^{2}(x)} \right) dx
```

```

r^{2} |&= s^{2} + t^{2},           \label{E:Pyth}\\
2u + 1 |&= v + w^{\alpha},       \label{E:alpha}\\
x |&= \frac{y + z}{\sqrt{s + 2u}}; \label{E:frac}

```

alignment points
of formulas

```

(2) r^2 = s^2 + t^2,
(3) 2u + 1 = v + w^\alpha,
(4) x = \frac{y + z}{\sqrt{s + 2u}};

```

Figure 3.1: Simple alignment: source and typeset.

```

+ \frac{1+ f(x)g(x)}{\sqrt{1 - \sin x}}
\right) \, dx\label{E:longInt}\\
&= \int \frac{1 + f(x)}{1 + g(x)} \, dx
- 2 \tan^{-1}(x-2)\notag
\end{align}

```

The rules for simple alignment are easy to remember.

Rule ■ Simple alignments

- Use the `align` environment.
 - Separate the lines with `\\`.
 - In each line, indicate the alignment point with `&`, one `&` per line. If the alignment point is adjacent to an `=`, `+`, and so on, place it *before* to ensure proper spacing.
 - Place a `\notag` command in each line that you do not wish numbered.
 - If no line should be numbered, use the `align*` environment.
 - Place a `\label` command in each numbered line you may want to reference with `\ref`, `\eqref`, or `\pageref`.
-




Figure 3.2: Annotated alignment: source and typeset.

Annotated alignment

Annotated alignment allows you to align formulas and their annotations, that is, explanatory text, separately (see Figure 3.2):

$$\begin{array}{ll}
 (6) & x = x \wedge (y \vee z) & \text{(by distributivity)} \\
 & = (x \wedge y) \vee (x \wedge z) & \text{(by condition (M))} \\
 & = y \vee z.
 \end{array}$$

This example is typed as

```

\begin{align}
x \&= x \wedge (y \vee z)
&\&\text{(by distributivity)}\label{E:DoAlign} \\
&= (x \wedge y) \vee (x \wedge z)
&\&\text{(by condition (M))} \notag \\
&= y \vee z. \notag
\end{align}

```

The rules for annotated alignment are similar to the rules of simple alignment. In each line, in addition to the alignment point marked by $\&$, there is also a mark for the start of the annotation: $\&\&$.

3.4.3 Cases

The `cases` construct is a specialized matrix. It has to appear within a `math` environment such as the `equation` environment (see Section 3.4.1) or the `align` environment (see Section 3.4.2). Here is a typical example:

$$f(x) = \begin{cases} -x^2, & \text{if } x < 0; \\ \alpha + x, & \text{if } 0 \leq x \leq 1; \\ x^2, & \text{otherwise.} \end{cases}$$

is typed as follows:

```
\[
  f(x)=
  \begin{cases}
    -x^{2}, & & \&\text{if } \$x < 0\$;}\&\&
    \alpha + x, & & \&\text{if } \$0 \leq x \leq 1\$;}\&\&
    x^{2}, & & \&\text{otherwise.}
  \end{cases}
\]
```

Notice how you can put inline math, opened and closed with `$`, inside the argument of a `\text` command.

The rules for using the `cases` environment are the same as for matrices. Separate the lines with `\\` and indicate the annotation with `&`.

Your first article and presentation

4.1 *The anatomy of an article*

To begin, we use the sample article `intrart.tex` (in the `samples` folder) to examine the anatomy of an article. Copy it over to the work folder or type it, and save it in the work folder as we discuss the parts of an article.

Every \LaTeX article has two parts, the preamble and the body. The *preamble* of an article is everything from the first line of the source file down to the line

```
\begin{document}
```

For a schematic view of an article, see Figure 4.1.

The preamble contains instructions affecting the entire document. The *only* required command in the preamble is the `\documentclass` command. There are other commands (such as the `\usepackage` commands) that must be placed in the preamble if they are used, but these commands do not have to be present in every document.

Here is the preamble of the introductory sample article:

```
% Introductory sample article: intrart.tex

\documentclass{amsart}
\usepackage{amssymb,latexsym}
\usepackage{graphicx}
\newtheorem{theorem}{Theorem}
\newtheorem{lemma}{Lemma}
\newtheorem{definition}{Definition}
\newtheorem{notation}{Notation}
```

The preamble specifies the *document class* and then the L^AT_EX enhancements, or *packages*, used in the article. The preamble can also specify additional commands that are used throughout the document, such as proclamation definitions, user-defined commands, and so on.

`intrart.tex` specifies the `amsart` document class. This class defines the format used by the AMS journals—and many others—for articles. L^AT_EX then loads two pack-




Figure 4.1: A schematic view of an article.

ages, `latexsym` and `amssymb`, that provide the names of some mathematical symbols. Finally, \LaTeX loads the `graphicx` package, which we need because of the illustration.

The preamble concludes with the *proclamations*. A proclamation is a theorem, lemma, definition, corollary, note, or other similar construct. The `intrart.tex` article defines four proclamations. The first of these,

```
\newtheorem{theorem}{Theorem}
```

defines the `theorem` environment, which then can be used in the body of the article, as explained in Section 4.2.3. The other three are similar. \LaTeX automatically numbers and formats proclamations.

The article proper, called the *body*, is the content of the `document` environment—it is between the lines

```
\begin{document}
```

and

```
\end{document}
```

as illustrated in Figure 4.1. The body of an article is split into several parts, starting with the *top matter* containing title page information and the abstract. The top matter follows the line

```
\begin{document}
```

and concludes with the line

```
\maketitle
```

Here is the top matter of the introductory sample article:

```
\title{A construction of complete-simple\\
distributive lattices}
```

```
\author{George~A. Menuhin}
```

```
\address{Computer Science Department\\
University of Winnebago\\
Winnebago, MN 53714}
```

```
\date{March 15, 2006}
```

```
\begin{abstract}
```

```
In this note, we prove that there exist
\emph{complete-simple distributive lattices,}
that is, complete distributive lattices
with only two complete congruences.
```

```
\end{abstract}
```

```
\maketitle
```

And here is the rest of the body of the introductory sample article with some commentary, exclusive of the bibliography:

```
\section{Introduction}\label{S:intro}
```

In this note, we prove the following result:

```
\begin{theorem}
```

There exists an infinite complete distributive lattice~ \mathbb{K} with only the two trivial complete congruence relations.

```
\end{theorem}
```

```
\section{The  $\Pi^*$  construction}\label{S:P*}
```

The following construction is crucial in the proof of our Theorem (see Figure~\ref{Fi:products}):

```
\begin{definition}\label{D:P*}
```

Let $D_{\{i\}}$, for $i \in I$, be complete distributive lattices satisfying condition~\textup{(J)}. Their Π^* product is defined as follows:

```
\[
```

$$\Pi^* (D_{\{i\}} \mid i \in I) = \Pi (D_{\{i\}}^{\{-\}} \mid i \in I) + 1;$$

```
\]
```

that is, $\Pi^* (D_{\{i\}} \mid i \in I)$ is $\Pi (D_{\{i\}}^{\{-\}} \mid i \in I)$ with a new unit element.

```
\end{definition}
```

```
\begin{notation}
```

If $i \in I$ and $d \in D_{\{i\}}^{\{-\}}$, then

```
\[
```

$$\langle \dots, 0, \dots, d, \dots, 0, \dots \rangle$$

```
\]
```

is the element of $\Pi^* (D_{\{i\}} \mid i \in I)$ whose i -th component is d and all the other components are 0 .

```
\end{notation}
```

See also Ernest~T. Moynahan~\cite{eM57a}.

Next we verify the following result:

```

\begin{theorem}\label{T:P*}
Let  $D_{\{i\}}$ ,  $i \in I$ , be complete distributive
lattices satisfying condition~\textup{(J)}.
Let  $\Theta$  be a complete congruence relation on
 $\Pi^* ( D_{\{i\}} \mid i \in I )$ .
If there exist  $i \in I$  and  $d \in D_{\{i\}}$  with
 $d < 1_{\{i\}}$  such that, for all  $d \leq c < 1_{\{i\}}$ ,
\begin{equation}\label{E:cong1}
\langle \dots, d, \dots, 0, \dots \rangle \equiv
\langle \dots, c, \dots, 0, \dots \rangle
\pmod{\Theta},
\end{equation}
then  $\Theta = \iota$ .
\end{theorem}

```

We include an illustration, `products.eps` or `products.pdf` (in your `samples` folder). We copy them over to the work folder and load the `graphicx` package. We name the illustration in the `figure` environment. The illustration must be in the graphic image file formats EPS or PDF (see Chapter 13.1.2). We left the argument of the `\caption` command empty—it normally contains the name or a description of the figure. The illustration is centered with the `\centering` command (see Section 6.3).

```

\begin{figure}[hbt]
\centering\includegraphics{products}
\caption{}\label{Fi:products}
\end{figure}

```

The `figure` environment *floats*, that is, \LaTeX decides where to place the typeset figure. We can influence \LaTeX 's choice (see Section 10.4.3).

Then we place a proof in a `proof` environment.

```

\begin{proof}
Since
\begin{equation}\label{E:cong2}
\langle \dots, d, \dots, 0, \dots \rangle \equiv
\langle \dots, c, \dots, 0, \dots \rangle
\pmod{\Theta},
\end{equation}
and  $\Theta$  is a complete congruence relation,
it follows from condition~(J) that
\begin{equation}\label{E:cong}
\langle \dots, d, \dots, 0, \dots \rangle \equiv
\bigvee ( \langle \dots, c, \dots, 0, \dots \rangle
\mid d \leq c < 1 ) \pmod{\Theta}.
\end{equation}

```

```
\end{equation}
```

Let $j \in I$, $j \neq i$, and let $a \in D_j^-$. Meeting both sides of the congruence `\eqref{E:cong2}` with $\langle \dots, a, \dots, 0, \dots \rangle$, we obtain that

```
\begin{equation}\label{E:comp}
  0 = \langle \dots, a, \dots, 0, \dots \rangle
      \text{\pod{\Theta}},
\end{equation}
```

Using the completeness of Θ and `\eqref{E:comp}`, we get:

```
\[
  0 \equiv \bigvee ( \langle \dots, a, \dots, 0,
    \dots \rangle \mid a \in D_j^- ) = 1
\text{\pod{\Theta}},
```

```
\]
```

hence $\Theta = \iota$.

```
\end{proof}
```

At the end of the body, the *bibliographic entries* are typed between the lines

```
\begin{thebibliography}{9}
```

and

```
\end{thebibliography}
```

There are fewer than 10 references in this article, so we tell \LaTeX to make room for single-digit numbering by providing the argument 9 to the `thebibliography` environment. We use 99 if the number of references is between 10 and 99. The typeset bibliography is titled References.

The bibliography of `intrart.tex` is structured as follows:

```
\begin{thebibliography}{9}
```

```
\bibitem{sF90}
```

Soo-Key Foo,

`\emph{Lattice Constructions}`,

Ph.D. thesis,

University of Winnebago, Winnebago, MN, December, 1990.

```
\bibitem{gM68}
```

George A. Menuhin,

```

\emph{Universal algebra}.
D.~Van Nostrand, Princeton, 1968.

\bibitem{eM57}
Ernest~T. Moynahan,
\emph{On a problem of M. Stone},
Acta Math. Acad. Sci. Hungar. \textbf{8} (1957),
455--460.

\bibitem{eM57a}
Ernest~T. Moynahan,
\emph{Ideals and congruence relations in
lattices}. II,
Magyar Tud. Akad. Mat. Fiz. Oszt. K\{o}zl.
\textbf{9} (1957), 417--434.

\end{thebibliography}

The body and the article end when the document environment is closed with

\end{document}

```

4.1.1 *The typeset sample article*

On the next two pages, you find the typeset `intrart.tex`, the introductory sample article.

A CONSTRUCTION OF COMPLETE-SIMPLE DISTRIBUTIVE LATTICES

GEORGE A. MENUHIN

ABSTRACT. In this note, we prove that there exist *complete-simple distributive lattices*, that is, complete distributive lattices with only two complete congruences.

1. INTRODUCTION

In this note, we prove the following result:

Theorem 1. *There exists an infinite complete distributive lattice K with only the two trivial complete congruence relations.*

2. THE Π^* CONSTRUCTION

The following construction is crucial in the proof of our Theorem (see Figure 1):

Definition 1. *Let D_i , for $i \in I$, be complete distributive lattices satisfying condition (J). Their Π^* product is defined as follows:*

$$\Pi^*(D_i \mid i \in I) = \Pi(D_i^- \mid i \in I) + 1;$$

that is, $\Pi^*(D_i \mid i \in I)$ is $\Pi(D_i^- \mid i \in I)$ with a new unit element.

Notation 1. *If $i \in I$ and $d \in D_i^-$, then*

$$\langle \dots, 0, \dots, d, \dots, 0, \dots \rangle$$

is the element of $\Pi^*(D_i \mid i \in I)$ whose i -th component is d and all the other components are 0.

See also Ernest T. Moynahan [4].

Next we verify the following result:

Theorem 2. *Let D_i , $i \in I$, be complete distributive lattices satisfying condition (J). Let Θ be a complete congruence relation on $\Pi^*(D_i \mid i \in I)$. If there exist $i \in I$ and $d \in D_i$ with $d < 1_i$ such that, for all $d \leq c < 1_i$,*

$$(1) \quad \langle \dots, d, \dots, 0, \dots \rangle \equiv \langle \dots, c, \dots, 0, \dots \rangle \pmod{\Theta},$$

then $\Theta = \iota$.

Proof. Since

$$(2) \quad \langle \dots, d, \dots, 0, \dots \rangle \equiv \langle \dots, c, \dots, 0, \dots \rangle \pmod{\Theta},$$

and Θ is a complete congruence relation, it follows from condition (J) that

$$(3) \quad \langle \dots, d, \dots, 0, \dots \rangle \equiv \bigvee (\langle \dots, c, \dots, 0, \dots \rangle \mid d \leq c < 1) \pmod{\Theta}.$$

2

GEORGE A. MENUHIN




FIGURE 1

Let $j \in I$, $j \neq i$, and let $a \in D_j^-$. Meeting both sides of the congruence (2) with $\langle \dots, a, \dots, 0, \dots \rangle$, we obtain that

$$(4) \quad 0 = \langle \dots, a, \dots, 0, \dots \rangle \quad (\Theta),$$

Using the completeness of Θ and (4), we get:

$$0 \equiv \bigvee \langle \langle \dots, a, \dots, 0, \dots \rangle \mid a \in D_j^- \rangle = 1 \quad (\Theta),$$

hence $\Theta = \iota$. □

REFERENCES

- [1] Soo-Key Foo, *Lattice Constructions*, Ph.D. thesis, University of Winnebago, Winnebago, MN, December, 1990.
- [2] George A. Menuhin, *Universal algebra*. D. Van Nostrand, Princeton, 1968.
- [3] Ernest T. Moynahan, *On a problem of M. Stone*, Acta Math. Acad. Sci. Hungar. **8** (1957), 455–460.
- [4] Ernest T. Moynahan, *Ideals and congruence relations in lattices*. II, Magyar Tud. Akad. Mat. Fiz. Oszt. Közl. **9** (1957), 417–434.

COMPUTER SCIENCE DEPARTMENT, UNIVERSITY OF WINNEBAGO, WINNEBAGO, MN 53714

4.2 *An article template*

In this section, you create an article template. To start a new article, open the template and start writing!

Make a copy of `intrart.tex` and give the copy an appropriate name. I named mine `gg.tex` (it is in the `samples` folder). Remember the naming rule (page 4): The name should have no spaces, no special characters, and end with `.tex`. So the name `my template.tex` is not good, but `MyTemplate.tex` is fine.

4.2.1 *Editing the top matter*

Edit the top matter to contain the relevant information, e.g., title and address, for your template. Here are some simple rules to follow.

Rule ■ Top matter

1. `\thanks` places an unmarked footnote at the bottom of the first page, for instance to acknowledge research support. If it is not needed, comment it out.
2. Separate the lines of your address with `\\`. Do not put a `\\` at the end of the last line.
3. `\date{\today}` typesets today's date. If you do not want *any* date to appear, comment out the `\date` command. For a specific date, such as March 15, 2006, type `\date{March 15, 2006}`.
4. The `\title` command is the only required command. The others are optional.

Actually, if you do not give the `\maketitle` command, even the `\title` command is optional. On the other hand, if you do give the `\maketitle` command and omit the `\title` command, then you get the error message

```
! Undefined control sequence.
<argument> \shorttitle
```

```
1.27 \maketitle
```

Now delete all the content of the article, leaving you with the skeleton. Here is the edited `gg.tex` (it is in your `samples` folder):

```
% GG's article template: gg.tex

\documentclass{amsart}
\usepackage{amssymb,latexsym}
\usepackage{graphicx}
```

```

\newtheorem{theorem}{Theorem}
\newtheorem{lemma}{Lemma}
\newtheorem{definition}{Definition}
\newtheorem{notation}{Notation}

\begin{document}
\title{Title!}
\author{George Gr\{"a\}tzer}
\address{Department of Mathematics\
         University of Manitoba\
         Winnipeg, MB R3T 2N2\
         Canada}
\date{\today}

\begin{abstract}
To come!
\end{abstract}

\maketitle

\section{Introduction}\label{S:intro}

\begin{thebibliography}{9}

\end{thebibliography}

\end{document}

```

I also made a version for a joint article with another author: `gg2.tex` (see the `samples` folder). It adds the lines

```

\author{Second author}
\address{line1\
         line2\
         line3\
         line4}

```

before the `\date` command.

When I start writing an article, I open `gg.tex` or `gg2.tex`, save it under a new name, and edit the top matter. Here are two more rules about the top matter to keep in mind:

Rule ■ Top matter (continued)

5. If necessary, break the title into separate lines with `\\`. Do not put a `\\` at the end of the last line.
 6. Multiple authors get separate `\author` and `\address` commands.
-

4.2.2 Sectioning

An article, as a rule, is divided into sections. To start the section Introduction, type

```
\section{Introduction}\label{S:intro}
```

after the `\maketitle` command. `Introduction` typesets as the title of the section. I use the convention that `S:` starts the label for a section, so the label is `S:intro` (or something similar). The section's number is automatically assigned by \LaTeX . You can refer to this section number with `\ref{S:intro}`:

In Section~\ref{S:intro}, we introduce

The command `\section*` produces an unnumbered section.

Sections have subsections, and subsections have subsubsections. The corresponding commands are

```
\subsection \subsubsection
```

Their unnumbered variants are

```
\subsection* \subsubsection*
```

4.2.3 Invoking proclamations

In the preamble of the article `intrart.tex`, we defined the theorem, lemma, definition, and notation proclamations. These proclamations define environments.

For example, you type a theorem within a `theorem` environment. The body of the theorem, that is, the part of the source file that produces the theorem, is typed between the lines

```
\begin{theorem}\label{T:xxx}
```

and

```
\end{theorem}
```

where `T:xxx` is the label for the theorem. You should replace `xxx` with a label that is somewhat descriptive of the contents of your theorem. \LaTeX automatically assigns a number to the theorem, and the theorem can be referenced by using a command of the form `\ref{T:xxx}`.

4.2.4 Inserting references

The works to be listed are placed in the bibliography. Below are typical entries for the most frequently used types of references, an article in a journal, a book, a Ph.D. thesis, and a technical report. For more examples, see the bibliographic template file, `bibl.tpl`, in the `samples` folder.

```
\begin{thebibliography}{9}
  \bibitem{sF90}
    Soo-Key Foo,
    \emph{Lattice Constructions},
    Ph.D. thesis,
    University of Winnebago, Winnebago, MN,
    December, 1990.
  \bibitem{gM68}
    George~A. Menuhin,
    \emph{Universal algebra}.
    D.~Van Nostrand, Princeton, 1968.
  \bibitem{eM57}
    Ernest~T. Moynahan,
    \emph{On a problem of M. Stone},
    Acta Math. Acad. Sci. Hungar. \textbf{8} (1957),
    455--460.
  \bibitem{eM57a}
    Ernest~T. Moynahan,
    \emph{Ideals and congruence relations in
    lattices.} II,
    Magyar Tud. Akad. Mat. Fiz. Oszt. K\~{o}zl.
    \textbf{9} (1957), 417--434.
\end{thebibliography}
```

Each item listed in the bibliography can be referenced in the body of the article. You reference with the `\cite` command. The argument is the argument of the `\bibitem` command. So to reference Menuhin's article, type

```
\cite{gM68}
```

which typesets as [2] since Menuhin's article is the second in the list. So

```
┌
└ this result was first published in [2]
```

is typed as

```
this result was first published in~\cite{gM68}
```

How you write each label is up to you, subject only to the rule in Section 10.4.2, provided the labels are unique. I use the convention that the label for a `\bibitem` consists of the initials of the author and the year of publication. For example, a publication by Andrew B. Reich in 1987 would have the label `aR87` (a second publication by that author from that year would be `aR87a`). For joint publications, the label consists of the initials of the authors and the year of publication. For example, a publication by John Bradford and Andrew B. Reich in 1987 would have the label `BR87`.

You have to arrange the references in your document's `thebibliography` environment in the order you wish to see them. \LaTeX only takes care of the numbering and the citations in the text.

4.3 *On using \LaTeX*

Now that you are ready to type your first article, we give you some pointers on using \LaTeX .

4.3.1 *\LaTeX error messages*

You probably make a number of mistakes in your first article. These mistakes fall into the following categories:

1. Typographical errors, which \LaTeX blindly typesets
2. Errors in mathematical formulas or in the formatting of the text
3. Errors in your instructions to \LaTeX , that is, in commands and environments

Typographical errors can be corrected by viewing and spell checking the typeset article, finding the errors, and then editing the source file.

Mistakes in the second and third categories probably trigger errors during the typesetting process, such as the math errors in Section 3.2. Some of these mistakes may have to be corrected before your article can be completely typeset.

We now look at some examples of the third class of errors by deliberately introducing a number of mistakes into the source file of the article `intrart.tex` (in your `samples` folder, source file on pages 35–41, and shown typeset on pages 42–43), and examining the error messages that occur.

When \LaTeX displays a `?` prompt, you can either try to continue typesetting the document by pressing Return, or type `x` to stop typesetting immediately. See Section D.4 for other options.

Experiment 1 In `intrart.tex`, go to line 20 by using your editor's Go to Line command and remove the closing brace so that it reads

```
\begin{abstract
```

When you typeset `intrart.tex`, L^AT_EX reports a problem:

```
Runaway argument?
{abstract In this note, we prove that there exist
\emph {complete-sim\ETC.
! Paragraph ended before \begin was complete.
<to be read again>
                                \par
1.26
```

Line 26 of the file is the line after `\end{abstract}`. The error message informs you that the name of the environment that ends before line 26 is not completed before the end of the paragraph. Press Return to tell L^AT_EX to typeset the remainder of the article, leaving out the abstract.

`Runaway argument?` is an error message that comes up often. It usually means that the argument of a command is either longer than expected or it contains material that the argument cannot accept. Most often a closing brace solves the problem, as in the experiment.

Experiment 2 Now correct line 20, then go to line 25 and change it from

```
\end{abstract}
```

to

```
\end{abstrac}
```

and typeset the article again. L^AT_EX informs you of another error:

```
! LaTeX Error: \begin{abstract} on input line 20
ended by \end{abstrac}.
```

```
1.25 \end{abstrac}
```

This is perfect. L^AT_EX correctly analyzes the problem and tells you where to make the change.

You may continue typesetting the article by pressing Return. L^AT_EX then gives you the message:

```
! Missing } inserted.
<inserted text>
                                }
1.25 \end{abstrac}
```

The missing `}` inserted is the “special brace” `\end{abstract}` (more about this in Section 5.3.2). Press Return. L^AT_EX recovers from this error and the article is typeset correctly.

Experiment 3 Instead of correcting the error in line 25, comment it out with

```
% \end{abstrac}
```

and also comment out the four lines of the figure environment using block comment. Introduce an additional error in line 96. This line reads

```
and  $\Theta$  is a complete congruence relation,
```

Change Θ to $Teta$:

```
and  $Teta$  is a complete congruence relation,
```

Now, when you typeset the article, \LaTeX reports

```
! Undefined control sequence.
```

```
<recently read>\Teta
```

```
1.96 and  $Teta$ 
```

```
      $ is a complete congruence relation,
```

Pressing Return results in the message

```
! LaTeX Error: \begin{abstract} on input line 20
ended by \end{document}.
```

```
Type H <return> for immediate help.
```

```
...
```

```
1.150 \end{document}
```

These two mistakes are easy to identify: $Teta$ is a misspelling of Θ , and since $\end{abstract}$ is missing, \LaTeX is trying to match

```
\begin{abstract}
```

```
with
```

```
\end{document}
```

Now undo the changes you made to lines 25 and 96. Uncomment the figure.

Experiment 4 In line 42, delete the closing brace of the \label command:

```
\begin{definition}\label{D:P*
```

This results in a message for line 54, the blank line following the paragraph, that

```
! Paragraph ended before \label was complete.
```

This is easy to understand. You cannot begin a new paragraph within the argument of a `\label` command.

Undo the change to line 42.

Experiment 5 Add a blank line following line 58:

```
\langle \dots, 0, \dots, d, \dots, 0, \dots \rangle
```

This change results in the message

```
! Missing $ inserted.
<inserted text>
          $
1.59
```

There can be no blank lines within a displayed math environment. L^AT_EX catches the mistake, but the message itself is misleading. Pressing Return does not help; you cannot recover from the error. Delete the blank line.

Experiment 6 Add a `$` somewhere in line 58 (such errors often occur when cutting and pasting formulas):

```
\langle $\dots, 0, \dots, d, \dots, 0, \dots \rangle
```

You get the message:

```
! Display math should end with $$ .
<to be read again>
          \protect
1.58 \langle $\dots
          , 0, \dots, d, \dots, 0, \dots \rangle
```

Maybe this could be more to the point?

Error messages from L^AT_EX are not always helpful, but there is always some information that can be gleaned from them. Try to identify the structure, that is, the command or environment, that causes the error—read the section of this book that describes that command or environment. This should help you correct the error. Keep in mind that the error could be quite far from the line L^AT_EX indicates, but it is always on or before that line in the source file.

If you have difficulty isolating a problem, block comment all but the paragraph you suspect might have problems. If necessary, split a large paragraph into smaller pieces.

Tip Typeset often.

To some extent, you can avoid having to isolate problems by following this tip. For instance, if I were to typeset *First Steps into L^AT_EX* [29], with the closing brace of the first `\caption` command on line 480 of the source file missing, I would get the error message

```
! Text line contains an invalid character.
1.1227 ...pletely irreducible^^?
```

where the reference is to line 1227, about 700 lines removed from the actual error. However, if the only thing I did before typesetting was to insert that figure with its incorrect caption command, at least I would know where to look for errors. If you make a dozen corrections and then typeset, you may not know where to start.

4.3.2 Logical and visual design

The typeset version of `intrart.tex` (pp. 42–43) looks impressive. To produce such articles, you need to understand that there are two aspects to article design: *visual* and *logical*.

As an example, let us look at a theorem from `intrart.tex` (see the typeset form of the theorem on page 43). You tell L^AT_EX that you want to state a theorem by using a `theorem` environment:

```
\begin{theorem}\label{T:P*}
Let  $D_{i}$ ,  $i \in I$ , be complete distributive
lattices satisfying condition~\textup{(J)}.
Let  $\Theta$  be a complete congruence relation on
 $\Pi^{*} ( D_{i} \mid i \in I )$ .
If there exist  $i \in I$  and  $d \in D_{i}$  with
 $d < 1_{i}$  such that, for all  $d \leq c < 1_{i}$ ,
\begin{equation}\label{E:cong1}
\langle \dots, d, \dots, 0, \dots \rangle \equiv
\langle \dots, c, \dots, 0, \dots \rangle
\pmod{\Theta},
\end{equation}
then  $\Theta = \iota$ .
\end{theorem}
```

The logical part of the design is choosing to define a theorem by placing material inside a `theorem` environment. For the visual design, L^AT_EX makes hundreds of decisions. Could you have specified all of the spacing, font size changes, centering, numbering, and so on? Maybe, but would you *want* to? And would you want to repeat that process for every theorem in your document?

Even if you did, you would have spent a great deal of time and energy on the *visual design* of the theorem rather than on the *logical design* of your article. The idea

behind \LaTeX is that you should concentrate on what you have to say and let \LaTeX take care of the visual design.

This approach allows you to easily alter the visual design by changing the document class (or its options, see Sections 11.5, 12.1.2, and 18.1). Section 11.1 provides some examples. If you code the visual design into the article—hard coding it, as a programmer would say—such changes are much harder to accomplish, for you and for the journal publishing the article.

4.4 Converting an article to a presentation

To produce a document in \LaTeX for use as a presentation, you have to output it as a PDF file. You make your presentation using a PDF viewer such as Adobe Reader or print the pages of the PDF file on transparencies and use a projector.

So a *presentation* is a PDF file. To display the presentation, connect your computer to a projector. Open the PDF file in Adobe Reader, put it in full screen mode. Then project the presentation a page at a time by pressing the space bar or the forward and back arrow keys.

In \LaTeX , you use a presentation package—really, a document class—to prepare such a PDF file. We deal with presentations in detail in Chapter 14, but as a quick introduction, we convert `intrart.tex` into a presentation.

For the conversion, we use the presentation package `FoilTeX`, while in Chapter 14 we discuss the `beamer` package. To use the `FoilTeX` package, we have to learn only one new command, `\foilhead`.

Open `intrart.tex`, save it as `intropres.tex` in the work folder. We introduce some changes to the document to prepare it for the conversion. Once you are satisfied with the changes made, the `tex` file created for `FoilTeX` is typeset so as to produce the PDF file. For `WinEdt`, click on the PDF `TeXify` icon. For `TeXShop`, just click on `Typeset`. For other \TeX installations, check your user manual on how to create a PDF output.

4.4.1 Preliminary changes

Make the following changes in the preamble, top matter, and abstract.

1. Change the first line to


```
% Introductory presentation:intropres.tex
```
2. Change the `documentclass` to `foils`.
3. Add the line


```
\usepackage{amsmath}
```

 after the `documentclass` line. We have to do this because `FoilTeX` does not automatically load the AMS math package.

4. Delete the definitions of theorem, lemma, and definition. `FoilTeX` redefines these.
5. Copy the address into the `\author` command:

```
\author{George~A. Menuhin\\
        Computer Science Department\\
        University of Winnebago\\
        Winnebago, MN 53714}
```

and delete the `\address` command. This may seem strange, but it is necessary because `FoilTeX` is based on a legacy document class that does not have an `\address` command (see Chapter 12).

6. Move the abstract after the `\maketitle` command, as was customary in legacy document classes.
7. Add the `[scale=2]` option to the `\includegraphics` command, so the command becomes

```
\centering\includegraphics[scale=2]{products}
```

`FoilTeX` uses fonts in 20 point size, twice the usual size. So it is appropriate that we scale up the illustration to 200%.

So the new version is

```
% Introductory presentation:intropres.tex

\documentclass{foils}
\usepackage{amsmath}
\usepackage{amssymb,latexsym}
\usepackage{graphicx}

\begin{document}
\title{A construction of complete-simple\\
        distributive lattices}
\author{George~A. Menuhin\\
        Computer Science Department\\
        University of Winnebago\\
        Winnebago, MN 53714}
\date{March 15, 2006}

\maketitle
\begin{abstract}
    In this presentation, we prove that there exist
```

```

\emph{complete-simple distributive lattices,}
that is, complete distributive lattices
with only two complete congruences.
\end{abstract}

```

Declarations in the body

In your L^AT_EX editor, perform four search and replace operations in the body of the article. Change all of the following:

1. {theorem} to {Theorem}
2. {lemma} to {Lemma}
3. {definition} to {Definition}
4. {proof} to {Proof}

FoⁱL_TE_X defines and uses the capitalized versions.

Sectioning

Comment out all the \section commands. FoⁱL_TE_X uses the \foilhead command to break the material into pages and also as a substitute for sectioning.

4.4.2 Making the pages

We cut the presentation into pages (transparencies or foils) by inserting as many page breaking commands of FoⁱL_TE_X, \foilhead{}, as seems appropriate. The argument of the command becomes the “title” for the page. If the argument is empty, the page has no title.

Add the \foilhead{The result} command after the abstract. This ends the title page and adds the title The result to the next page.

See the intropres.tex document for all the other \foilhead{} commands we have added.

4.4.3 Fine tuning

We have eliminated the equation numbering, because it would make the equations too wide. Also, in a presentation, references to another page are not recommended. We made some additional changes to accommodate that we have fewer characters per line. Compare the documents intrart.tex and intropres.tex to see all the changes. Note how in the PDF file the fonts are automatically changed to sans serif, because sans serif text is easier to read when projected. The font size is 20pt, twice the size of the font in the article.

Of course, `intropres.tex` is not the most elegant presentation. But I hope it helps you to make your first presentation. On pages 57 and 58, we show the first two pages of this presentation.

There are, of course, a number of useful commands in `FoilTEX` in addition to the one we used, `\foilhead`. We did not even do justice to this one command. It has an optional argument to enlarge or shrink the space between the header and the body of the foil. So

```
\foilhead[-.5in]{A diagram}
```

shrinks that space by half an inch. This is especially useful with large diagrams.

For numerous other features of `FoilTEX`, see the user manual [33].

A construction of complete-simple distributive lattices

George A. Menuhin
Computer Science Department
University of Winnebago
Winnebago, MN 53714

March 15, 2006

Abstract

In this presentation, we prove that there exist *complete-simple distributive lattices*, that is, complete distributive lattices with only two complete congruences.

The result

In this presentation, we prove the following result:

Theorem 1. *There exists an infinite complete distributive lattice K with only the two trivial complete congruence relations.*

Installation

In case you do not already have a \LaTeX installation, in Sections A.1 and A.2, we describe how to install \LaTeX on your computer, a PC or a Mac. The installation is much easier if you obtain \TeX Live 2007 (or later) from the \TeX Users Group, TUG (see Section E.2). It contains both the \TeX implementations we discuss.

No installation is given for UNIX computers. The attraction of UNIX to its users is the incredibly large number of options, from the UNIX dialect, to the shell, the editor, and so on. A typical UNIX user downloads the code and compiles the system. This is obviously beyond the scope of this book. Nevertheless, \TeX Live 2007 (or later) from the \TeX Users Group supplies the compiled (binaries) of \LaTeX for a number of UNIX variants.

First read Chapter 1, so that in this Appendix you recognize the terminology we introduce there. I will assume that you become sufficiently familiar with your \LaTeX distribution to be able to perform the editing cycle with the sample documents.

A.1 *L^AT_EX on a PC*

On a PC, most mathematicians use MiKTeX and the editor WinEdt. So it seems appropriate that we start there.

A.1.1 *Installing MiKTeX*

If you made a donation to MiKTeX or if you have the T_EX Live 2007 (or later) from the T_EX Users Group, then you have a CD or DVD with the MiKTeX installer. Installation then is in one step and very fast. In case you do not have this CD or DVD, we show how to install from the Internet. To begin, go to the MiKTeX home page:

<http://miktex.org>

and under the Download/Install click on the version you want to install.¹ You are directed to the MiKTeX download page, where you click on Download MiKTeX Net Installer. This takes you to a list of the download sites, called “mirrors”. Choose one geographically close to you and click Download next to your pick. You are asked whether to Run or Save the installer application. Choose Save to save and now you have the setup application on your computer.

Run setup and the MiKTeX Setup Wizard should start automatically. Then click Next and choose the task, Download only. Click Next again to choose the size of the download and choose Complete MiKTeX. Again you have to choose a download site, and click Next a few more times, then Start, and the download starts. When it is complete, almost 35,000 files later, click Close. Now you have the files you need in the next step.

The next task is installation. Run setup again, and up comes the Wizard. Click Next, and the task Install MiKTeX is selected for you. Click Next, make sure you select Complete MiKTeX. Click Next a few more times, select the default paper size, click Start, and the installation starts. When it is finished, click Close.

A.1.2 *Installing WinEdt*

You can download WinEdt from its Web site and use it for 30 days before you pay the license fee. We now install WinEdt from the CD you are sent after you pay the license fee. Go to License and Registration at

<http://www.winedt.com>

Put the WinEdt installer CD in the DVD drive. The WinEdt Setup Wizard starts automatically. After accepting the licence, click Next a few times until WinEdt is installed and then click Finish.

After installation, the WinEdt Configuration Wizard

¹We follow the instructions for MiKTeX 2.5. Hopefully, this will also assist you with later versions.

starts automatically. Click on the `File Associations` tab and click on `Modify file type associations...` under `Current User`, which is down the right side of the window, and then click `OK`. This gives all `TEX` files a lion icon and automatically associates them with `WinEdt` so that double clicking a `TEX` file automatically opens it in `WinEdt`. Clicking `OK` to close the Wizard.

`WinEdt`'s claim to fame is its incredible customizability. Once you become familiar with the basic operations, you can make `WinEdt` behave the way you like.

A.1.3 *The editing cycle*

In Section 1.2 you created the `work` folder for your work files. Start `WinEdt` by double clicking the `WinEdt` icon and open the file `note1.tex` in `work`, see the top half of Figure A.1. Observe:

- In the right-hand corner, under the `X` button, the close application button, there is a small black `x`. All windows of `WinEdt` have such an `x`, this is the *close window* button.
- There are two rows of icons. The seventh from the right in the first row, a darkened lion's head, is the `TeXify` button, use it to typeset your `LATEX` file. If you are not sure what an icon represents, let the cursor hover over it, and a brief description appears.
- A blue arrow in the left margin points at the line where the cursor is.

Click on the `TeXify` icon. `MiKTeX` typesets `note1.tex` and produces another file, `note1.dvi`. The new file is displayed by the application `Yap`, which was automatically installed for you with `MiKTeX`. Rearrange the `WinEdt` and `Yap` windows. You should get an arrangement similar to the bottom half of Figure A.1.

A.1.4 *Making a mistake*

`WinEdt` tells you if there is a mistake in your source file. To see what happens, click on the `WinEdt` window, and add a `\` in line 11 of `note1.tex`, so that `personally` reads `\personally`. This makes `\personally` a command, which is a mistake (see Chapter 2). Click on the `TeXify` icon. We get the `TeXify ...` window, as in the top part of Figure A.2. At the `?` prompt, type `x` for “exit” and press `Return`.² You now see three windows, as shown in the bottom half of Figure A.2. The `Yap` window is mostly covered up. There is a new window, `note1.log`, the log window, in which the information from the `TeXify ...` window is recorded. In the `WinEdt` window, the blue arrow line pointer on the left indicates the offending line, and the mistake, `\personally`, is highlighted in red. Correct the mistake by deleting `\`, click on `TeXify`, and you are back in business.

²The user, recorded on Figure A.2, typed `s` for “scroll mode”. `LATEX` then completes the typesetting without stopping for errors (see Section D.4).





Figure A.1: note1.tex opened in WinEdt and typeset.





Figure A.2: The mistake identified and localized (showing the log window).

A.1.5 *Three productivity tools*

Now we see how the three productivity tools introduced in Section 1.4 are implemented in WinEdt and MiKTeX.

Synchronization This is known as *inverse search* in WinEdt and MiKTeX. To set it up, open Yap, for example, by Texifying the document `note1.tex`. Choose the menu item `View>Options>Inverse DVI Search`. A list now displays the editors detected. Select WinEdt, click Apply, and click OK. You are done.

- To jump from the typeset file in Yap to the source file in WinEdt, double click a word in the typeset file.
- To jump from the source file to the typeset file, click on the `DVI Search` icon, the magnifying glass with the green leaf attached to the handle. You then jump to the typeset file, where a marker indicates the beginning of the typeset version of the source line the cursor is on.

Block comment Select a number of lines in a source document and choose the menu option `Edit>Move/Fill>Insert comment`. Block uncomment is done with `Edit>Move/Fill>Remove comment`.

Go to line This is done with `Search>Go to Line...`

The icons and menu options all have keyboard equivalents. For instance, `Go to line` is `Ctrl+G` and `TeXify` is `Ctrl+Shift` and then press `x`.

A.1.6 *An important folder*

When using MiKTeX, where do you put new style files and packages?

You can always place these files in your working folder. This is the simplest, but they will not be available when working with files outside that folder.

If you want these files accessible everywhere (from all folders), then make a new folder in the `LocalTeXMF` folder tree, say

```
C:\LocalTeXMF\MyStyles
```

and place these files there. In order for MiKTeX to find these files, you now need to update the MiKTeX `FileName Database`. Do this:

```
All Programs>MiKTeX>MiKTeX Options>Refresh FNDB
```

or access it directly via the drop down menus from within WinEdt:

```
Accessories>MiKTeX Options
```

The best way to install new packages from CTAN is via the `Package Manager`, which is accessed via

All Programs>MikTeX>Package Manager

The Package Manager downloads the files from a CTAN mirror of your choice, then installs all files in their correct folders and updates MikTeX's filename database.

It is a good idea to run the MikTeX Update Wizard on a regular basis to keep your system up to date:

All Programs>MikTeX>MikTeX Update Wizard

A.2 *L^AT_EX on a Mac*

A.2.1 *Installations*

For the Mac, we install MacTeX,³ which consists of the TUG's T_EX Live and Richard Koch's TeXShop. If you have T_EX Live (see Section E.2), put the DVD in your computer's DVD drive and follow the simple instructions. In a few minutes you are done. Otherwise, go to

<http://www.tug.org/mactex/>

and in the Downloading section, click on MacTeX-2007. After downloading about 700 MBs, you get the MacTeX-2007 "disk image" that contains the mactex installer package. The disk image should open and the application MacTeX-2007.mpkg should start automatically. A few more clicks—as in all Mac installations—and you are done.

The spelling checker

Finally, get the spell checker cocoAspell by Anton Leuski by going to

<http://people.ict.usc.edu/~leuski/cocoaspell/home.html>

and clicking on the download link, cocoAspell. This downloads the disk image cocoAspell.dmg, containing the installation package cocoAspell.mpkg. Follow the same process as above to mount this. Then double click on the installer package and follow the instructions.

In the Apple menu, choose System Preferences..., where you find a new one, Spelling. Double click on it, and choose a dictionary. I use the dictionary English(United States). You should also select the filters you need. They are explained on the page you obtain by clicking on the Filter button. I selected Texinfo and TeX/LaTeX. You may have to restart the computer for the spelling checker to work.

To invoke the spelling checker, select a word and press Command+Shift and :. It suggests a correct spelling. You can also add words to the dictionary.

To learn more about the dictionaries, read the documents in

</Library/Application Support/cocoAspell/aspell6-en-6.0-0/doc/>

³We follow the instructions for MacTeX-2007. Hopefully, this will also assist you with later versions.

A.2.2 Working with TeXShop

Custom settings

In due course, you can fully customize TeXShop as an advanced user. But to begin, there are just a few things to do. In the TeXShop menu choose Preferences... to open the TeXShop Preferences. To set the default font for the source files in TeXShop, click on the Document tab. Under Document Font click Set..., which brings up the Font window. Choose a font and size for the source files that is easy on your eyes. I use Courier and 12. Close the Font window.

Make sure that under Editor all items except Auto Complete are selected.

Now click the Preview tab and in the Preview Window Magnification enter a number for the magnification to be used for viewing the typeset version—I use 150. Once you type in the number, press Set. For Default Mouse Mode, choose Select Text. For Default Page Style, choose Multi-Page.

Under After Window Resize, choose Fixed Magnification. Then click on OK. Close the TeXShop Preferences window.

When you become more familiar with TeXShop, you may want to revisit these settings.

Changing a document for TeXShop

If

- you use the `graphicx` package, see `intrart.tex` in the `samples` folder as an example, and
- your document contains illustrations that have been saved as EPS graphics and included with the `\includegraphics` command,

then add the line

```
\usepackage{epstopdf}
```

in the preamble below the line


```
\usepackage{graphicx}
```

If you have many illustrations, it is preferable to open all the illustrations with TeXShop or Preview and save them in PDF format. Also, make sure that the extensions are not given in the `\includegraphics` commands, that is,

```
\usepackage{graphicx}
\includegraphics{products.eps}
```

is changed to

```
\usepackage{graphicx}
\includegraphics{products}
```

Figure A.3: The document `note1.tex`: the source and the typeset version.

A.2.3 *The editing cycle*

In your Document folder, you created the work folder (see page 4). We are going to work with the document `note1.tex` in the work folder.

To start TeXShop, double click on `TeXShop.app` in the Applications folder, select the menu `File>Open...`, and navigate to the folder

```
Documents/work/note1.tex
```

Open the document.

In the upper left corner of the source window, click the Typeset button. A second window opens, the *preview window*, showing `note1.pdf`, the typeset version of `note1.tex`. Unlike WinEdt, discussed in Section A.1, which produces a file called `note1.dvi`, TeXShop produces a PDF file, `note1.pdf`.

Figure A.3 shows the two windows. At the top, you see TeXShop's seven menus. For this introduction we ignore all but two menu options. You should use the Help menu to learn more and the `Macros Help` in the Help window along with the `Macro Editor` (open it with `Macros>Open Macro Editor...`) to become more productive.

A.2.4 *Making a mistake*

TeXShop tells you if there is a mistake in your source file. Open `note1.tex` again and introduce a silly error, say, in the line `\documentclass{amsart}`, delete the closing brace, so it reads `\documentclass{amsart`. A new window—the third!—pops up, called `note1 console`, see Figure A.4. This is the log window (see Section 1.3). Click on the button `Goto Error` and the cursor is placed in the source document pretty close to the error. Now you can correct the error and typeset again.

A.2.5 *Three productivity tools*

Now we see how the three productivity tools introduced in Section 1.4 are implemented in TeXShop.

Synchronization Command-click on a word in the source window. The preview window shows the corresponding typeset phrase circled in red. Similarly, command-click on a word in the preview window and the corresponding source phrase is highlighted in yellow—it helps to click on text with no \LaTeX commands close by.

Block comment Select a number of lines in a source document, and choose the menu option `Format>Comment`. All the lines, the whole block, are commented out. The reverse is done with `Format>Uncomment`.

Go to line This is done with `Edit>Line Number...`

Figure A.4: The `note1.tex` console (log window).

Buttons and menu options all have keyboard equivalents. For instance, Block comment is Command + { and Go to line is Command + L.

A.2.6 *An important folder*

Create the `texmf` folder in the Library folder of your home folder—**not** the other Library folder, which is in the same folder as Applications. In `texmf`, create the `tex` folder, wherein you create the `latex` folder. Put all your personal (see Section 15.3) and additional `sty` files here.